



RAVENOL 2-Takt-Öl NOT SELFMIX



SPECIFICATIONS API SA

RAVENOL 2-Takt-Öl NOT SELFMIX is a mineral high quality two-stroke oil for conventional 2-stroke engines without self-mixing. This unblended oil is produced from carefully selected, pure mineral raffinates. It is resistant to oxidation, non-foaming and has excellent viscosity-temperature characteristics.

ART.-NR. 1153101

1 L | 1153101-001
4 L | 1153101-004
10 L | 1153101-010
20 L | 1153101-020
20 L | 1153101-B20
1000 L | 1153101-700

Due to the low pour point, this oil can be used in low as well as high temperatures and ensures an impeccable lubrication.

Application Notes

RAVENOL 2-Takt-Öl NOT SELFMIX is applicable for all conventional two-stroke engines, for which self-mixing is not specified.

Characteristics

RAVENOL 2-Takt-Öl NOT SELFMIX offers:

- Excellent viscosity-temperature characteristics
- Good shear stability
- Outstanding oxidation stability
- Good demulsification characteristics

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	896,0	EN ISO 12185
Colour		gelbbraun	visual
Viscosity at 100°C	mm ² /s	15,7	DIN 51 562
Viscosity at 40°C	mm ² /s	165,8	DIN 51 562
Viscosity index VI		97	DIN ISO 2909



Property	Unit	Data	Audit
Pourpoint	°C	-24	DIN ISO 3016
Flash point (COC)	°C	254	DIN ISO 2592

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 16. August 2019