



## RAVENOL ATF+4® Fluid



### FABRICATION SYNTHETIC

**APPROVALS** LICENSE-NO. 40630041 FCA US LLC (FORMERLY: CHRYSLER GROUP LLC)

**RECOMMENDATIONS** MS-9602 | MOPAR 68218057GA (BISHER: 0501357AA, 051035227EA/05013457GA) | MOPAR 68218058GA (BISHER: 05103527EA/05013457GA) | MOPAR 68218054GA (BISHER 680474406MA, 68087385EA) | FIAT 9.55550-AV4

### ART.-NR. 1211100

1 L | 1211100-001  
4 L | 1211100-004  
10 L | 1211100-010  
20 L | 1211100-020  
20 L | 1211100-B20  
60 L | 1211100-060  
60 L | 1211100-D60  
208 L | 1211100-208  
208 L | 1211100-D28  
1000 L | 1211100-700

**RAVENOL ATF+4® Fluid** is a synthetic, licensed automatic transmission fluid ATF with an unique additive package for Fiat-Chrysler, Jeep and Dodge automatic transmission.

**RAVENOL ATF+4® Fluid** guarantees maximum wear protection in all operating conditions.

**RAVENOL ATF+4® Fluid** is mixable with all **ATF+4®**, **ATF+2®** or **ATF+3®** transmission oil.

## Application Notes

**RAVENOL ATF+4® Fluid** is recommended for refilling and fill up automatic transmission oil for Fiat-Chrysler, Dodge, Plymouth, RAM, Jeep and Eagle vehicles with automatic Transmission.

**RAVENOL ATF+4® Fluid** achieves the warranty of FCA US LLC (Fiat Chrysler Automobiles) and is released with Licence-No. 40630041.

**RAVENOL ATF+4® Fluid** meets the requirements of current and previous standards for Fiat-Chrysler, Dodge, Plymouth, Jeep and Eagle automatic transmission oil.

## Characteristics

**RAVENOL ATF+4® Fluid** offers:

- Better protection and better performance than ATF+3®
- Extended transmission life
- Reduces maintenance costs
- Better shift quality through a consistent viscosity profile
- Better cold flow properties
- Smooth switching at low temperatures



- Less transmission wear when operating at low temperatures
- Better oxidation stability and thermal stability than the previous ATF+3®
- Longer oil life period
- Lower oil consumption
- Better fuel economy
- Longer oil change intervals (has been tested extensively with oil change intervals of about 160,000 km)



Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	844	EN ISO 12185
Colour		rot	visual
Viscosity at 100°C	mm <sup>2</sup> /s	7,51	DIN 51562
Viscosity at 40°C	mm <sup>2</sup> /s	33,24	DIN 51562
Viscosity index VI		204	DIN ISO 2909
Pourpoint	°C	-51	DIN ISO 3016
Brookfield Viscosity	mPa*s	8380	DIN 51 377
Flash point	°C	198	DIN ISO 2592

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 23. August 2019