



RAVENOL ATF Fluid Type F



ART.-NR. 1213105

1 L | 1213105-001
4 L | 1213105-004
10 L | 1213105-010
20 L | 1213105-020
20 L | 1213105-B20
60 L | 1213105-060
60 L | 1213105-D60
1000 L | 1213105-700

FABRICATION MINERAL

RECOMMENDATIONS FORD TYPE M2C-33F/G | MOTORCRAFT XT-1-QF |
VOLVO 97330

RAVENOL ATF Fluid Type F is an universal ATF (automatic transmission fluid) for use as a speciality transmission oil for Ford, Borg Warner and Volvo. **RAVENOL ATF Fluid Type F** is designed based on refined base oils with a special additive treatment and inhibition ensuring trouble-free function.

Application Notes

RAVENOL ATF Fluid Type F is suitable for use as a speciality transmission oil for Ford, Borg Warner and Volvo.

Use according to aggregate manufacturer operating instructions in: automatic transmissions, fluid turbo coupling, servo clutches and other hydrostatic and hydrodynamic Systems.

Characteristics

RAVENOL ATF Fluid Type F offers:

- Universal use, therefore minimising the risk of confusion and making stock-keeping easy.
- Good lubricating ability even in low temperatures during winter.
- Stable lubricating film under extreme stress in midsummer resulting in comparatively low wear throughout the change interval.
- Excellent viscosity-temperature properties.
- High thermal resilience.
- Compatible with brand name ATFs.
- Non-foaming even in extreme conditions.
- Reliable protection against wear, sludge, corrosion and adhesion.
- FZG test: Reaches failure load stage 12 before and after shearing.



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	848,0	EN ISO 12185
Colour		rot	visual
Viscosity at 100°C	mm ² /s	7,3	DIN 51 562
Viscosity at 40°C	mm ² /s	34,3	DIN 51 562
Viscosity index VI		185	DIN ISO 2909
Pourpoint	°C	-45	DIN ISO 3016
Flash point	°C	210	DIN ISO 2592

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 20. October 2020