



RAVENOL ATF JF405E



ART.-NR. 1211118

1 L	1211118-001
4 L	1211118-004
10 L	1211118-010
20 L	1211118-020
20 L	1211118-B20
60 L	1211118-060
60 L	1211118-D60
208 L	1211118-208
208 L	1211118-D28
1000 L	1211118-700

FABRICATION SYNTHETIC

RECOMMENDATIONS HYUNDAI JWS3314 | SUZUKI 99000-22A80-025 | SUZUKI ATF 3314 | HYUNDAI 45000-34D00 | HYUNDAI 04500-00130 | HYUNDAI 04500-00430 | ESSO JWS3314

RAVENOL ATF JF405E is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

RAVENOL ATF JF405E is an ATF (automatic transmission fluid) for modern 4-speed automatic transmission JF402E and JF405E of Jatco for Mazda AZ-Wagon, Spiano, KIA Picanto/Morning, Chevrolet Matiz, Opel Agila, Hyundai Atos, Suzuki Wagon-R, Cervo, Nissan Moco, Pino. Guarantees maximum wear protection in all operating conditions.

RAVENOL ATF JF405E is red colored.

Application Notes

RAVENOL ATF JF405E is for use in 4-Stroke automatic transmission JF405E or JF402E from Jatco for Hyundai SANTRO 1.1L, Hyundai Atos, KIA MORNING 1.0L and 1.1L, KIA PICANTO 1.0L, KIA VISTO 0.8L, Nissan MARCH 1.0L, Nissan Moco, Nissan Pino, Opel Agila 1.0L, Suzuki Alto 0.7L, Suzuki Cervo 0.7L, Suzuki Cultus 1.3L, Suzuki Kei 0.7L, Suzuki Lapin 0.7L, Suzuki MR Wagon 0.7L, Suzuki Palette 0.7L, Suzuki Wagon R 0.7L, Daewoo Matiz, Mazda AZ-Wagon, Mazda Laputa.

Characteristics

RAVENOL ATF JF405E offers:

- a very good lubricating ability even at low temperatures in winter
- a high, stable viscosity index
- a very good oxidation stability
- as far as possible protection against corrosion and foam formation
- good balanced coefficient of friction
- a high thermal and oxidative stability
- a excellent cooling capacity



RAVENOL special transmission fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the

product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult

our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to

malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission. Ravensberger

Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	847,0	EN ISO 12185
Colour		rot	visual
Pourpoint	°C	-54	DIN ISO 3016

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 16. January 2020