



## RAVENOL ATF JF506E



ART.-NR. 1211119

1 L | 1211119-001  
4 L | 1211119-004  
10 L | 1211119-010  
20 L | 1211119-020  
20 L | 1211119-B20  
60 L | 1211119-060  
60 L | 1211119-D60  
208 L | 1211119-208  
208 L | 1211119-D28  
1000 L | 1211119-700

**FABRICATION SYNTHETIC**

**RECOMMENDATIONS** LAND ROVER STC50531 | FORD WSS-M2C922-A1 FÜR DURASHIFT 5F31J | LAND ROVER LRN402 | ATF TYPE 3100 PL085 | LAND ROVER STC53016 | JAGUAR C2S 12120 | ATF TYPE K17 | ATF N402 | VW G052990A2 FOR 09A AND 09B 5-SPEED TIPTRONIC

**RAVENOL ATF JF506E** is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic Transmission.

**RAVENOL ATF JF506E** is an ATF (automatic transmission fluid) for modern 5-speed automatic transmission JF506E of Jatco for FORD Mondeo, Galaxy, Land Rover Freelander, Rover 75, VW Bora, Sharan, Golf, Jaguar X-Type, Seat Alhambra.

**RAVENOL ATF JF506E** is red colored.

## Application Notes

**RAVENOL ATF JF506E** is for use in 5-Stroke automatic transmission JF506E of Jatco for FORD Mondeo, Galaxy, Land Rover Freelander, Rover 75, VW Bora, Sharan, Golf, Jaguar X-Type, Seat Alhambra.

## Characteristics

**RAVENOL ATF JF506E** offers:

- a very good lubricating ability even at low temperatures in winter
- a high, stable viscosity index
- a very good oxidation stability
- as far as possible protection against corrosion and foam formation
- good balanced coefficient of friction
- a high thermal and oxidative stability
- a excellent cooling capacity

RAVENOL special transmission fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the

product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult



our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission. Ravensberger Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.



Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	847,0	EN ISO 12185
Colour		rot	visual
Pourpoint	°C	-51	DIN ISO 3016

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 16. January 2020