



## RAVENOL ATF M 9-Serie



ART.-NR. 1211108

1 L	1211108-001
4 L	1211108-004
10 L	1211108-010
20 L	1211108-020
20 L	1211108-B20
60 L	1211108-060
60 L	1211108-D60
208 L	1211108-208
208 L	1211108-D28
1000 L	1211108-700

**FABRICATION SYNTHETIC**

**APPROVALS** MB-APPROVAL 236.14 (001 989 68 03 10)

**RECOMMENDATIONS** MB 236.12 (001 989 45 03 10), MB 236.10 (001 989 21 03 10)

**ATF Professional Line**

**RAVENOL ATF M 9-Serie** is automatic transmission oil ATF, produced on the basis of hydrocrack oils and PAO with special additives and inhibition which guarantees a perfect function of the automatic transmission.

**RAVENOL ATF M 9-Serie** is one of the ATF (Automatic Transmission Fluid) of the newly developed generation for all 7-motion automatic transmission of Mercedes Benz. A maximum wear protection in every operating state is guaranteed.

## Application Notes

**RAVENOL ATF M 9-Serie** was developed for use in the newly developed NAG2V Sport transmission, 7G-Tronic (Template 722.9 / W7A 700 / NAG2), also for 5-gear transmission (Template 722.6 / W5A 580 / NAG1). It is backwardly compatible for all earlier versions of Mercedes-Benz 4- und 5-gear passenger car transmission (Template 722.3, 722.4, 722.5) in the exception of 5-motion CVT-Automatic transmission (Template 722.7 / FAG) of the A-Class (W168) and the Vaneo (W414).

## Characteristics

**RAVENOL ATF M 9-Serie** offers:

- a very good lubricating ability even at low temperatures in winter
- a high, stable viscosity index
- a very low pour point
- a very good oxidation stability
- protection against corrosion and foam formation
- good balanced coefficient of friction
- a high thermal and oxidative stability
- a excellent cooling capacity



- a excellent shear stability
- lowest evaporation losses
- a neutral behaviour against sealing materials
- a neutral behaviour because of inhibition against non ferrous metals
  
- RAVENOL special transmission fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data
- **Please note:** RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle.
  
- Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission.
  
- Ravensberger Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.



Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	844	EN ISO 12185
Colour		rot	visual
Pourpoint	°C	-54	DIN ISO 3016

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 11. March 2020