



RAVENOL ATF RED-1



FABRICATION SYNTHETIC

RECOMMENDATIONS ATF RED-1 | KIA UM040-CH020 | KIA 04500-00140 | HYUNDAI 04500-00140

RAVENOL ATF RED-1 is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

ART.-NR. 1211117

1 L	1211117-001
4 L	1211117-004
10 L	1211117-010
20 L	1211117-020
20 L	1211117-B20
60 L	1211117-060
60 L	1211117-D60
208 L	1211117-208
208 L	1211117-D28
1000 L	1211117-700

RAVENOL ATF RED-1 is an ATF (automatic transmission fluid) of the latest generation of modern 5-speed automatic transmission A5SR1 and A5SR2 of Hyundai Powertech for KIA Sorento, KIA Mohave, Hyundai Genesis Coupe, Hyundai H-1. Guarantees maximum wear protection in all operating conditions.

RAVENOL ATF RED-1 is red colored.

Application Notes

RAVENOL ATF RED-1 is for use in 5-Stroke automatic transmission A5SR1 and A5SR2 of Hyundai Powertech für KIA Sorento, KIA Mohave, Hyundai Genesis Coupe, Hyundai H-1, Hyundai Grand Starex, Hyundai i800.

Characteristics

RAVENOL ATF RED-1 offers:

- a very good lubricating ability even at low temperatures in winter
- a high, stable viscosity index
- a very good oxidation stability
- as far as possible protection against corrosion and foam formation
- good balanced coefficient of friction
- a high thermal and oxidative stability
- an excellent cooling capacity

RAVENOL special transmission fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data.

Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information.



Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle.
Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission.
Ravensberger Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	847,0	EN ISO 12185
Colour		rot	visual
Pourpoint	°C	-54	DIN ISO 3016

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 22. August 2019