



RAVENOL Bettbahnöl 220



ART.-NR. 1350378

20 L | 1350378-020

SPECIFICATIONS DIN 51 502 CGLP, DIN 51 517-3 CLP, DIN 51 524-2 HLP
FABRICATION MINERAL

RAVENOL Bettbahnöl 220 is mineral slide way oil CGLP.

RAVENOL Bettbahnöl 220 is characterized by good lubricating and sliding properties as well as high tackiness.

RAVENOL Bettbahnöl 220 is formulated with mineral base oils and contains additives and corrosion inhibitors to prevent rust formation and stains on slide ways and track surfaces.

RAVENOL Bettbahnöl 220 is compatible with most of drilling-, cutting or grinding emulsions. The lubricant film of the slide way oil is not washed off.

Application Notes

RAVENOL Bettbahnöl 220 can be used for all types of lubrication systems such as pressure, circulating or central lubrication. If necessary it can be applied manually. It can also be used for lubricating bearings and gear boxes.

Characteristics

RAVENOL Bettbahnöl 220 offers:

- Very good stick-slip characteristics
- High tackiness
- Good corrosion protection, no rust and stain formation
- Resistance to aqueous metalworking fluids
- Good demulsification

| Property | Unit | Data | Audit |
|-----------------|-------------------|-------|--------------|
| Density at 20°C | kg/m ³ | 890,0 | EN ISO 12185 |
| Colour | | gelb | visual |



| Property | Unit | Data | Audit |
|--------------------|--------------------|-------|--------------|
| Viscosity at 100°C | mm ² /s | 18,7 | DIN 51 562 |
| Viscosity at 40°C | mm ² /s | 216,7 | DIN 51 562 |
| Viscosity index VI | | 96 | DIN ISO 2909 |
| Pourpoint | °C | -15 | DIN ISO 3016 |
| Flash point (COC) | °C | 250 | DIN ISO 2592 |

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 20. February 2019