



RAVENOL Bettbahnöl 32



ART.-NR. 1350374

208 L | 1350377-208

SPECIFICATIONS DIN 51 502: CGLP | AFNOR E 60-203 L-G/HG | GB 11118.1-94 L-HG/HM | ISO 6743-6 CKC | ISO 6743-13 GA/GB | ISO 11158 HG/HM | ISO 19378 GA/GB | SAE MS 1007 TYP E | SH/T 0361-98 L-G | DIN 51 517 TEIL 2 | DIN 51 517 PART 3

FABRICATION MINERAL

RECOMMENDATIONS EATON VICKERS M-2950-S | GENERAL MOTORS LS2 LW-03-1-04 | FIVES CINCINNATI P-53

RAVENOL Bettbahnöl 32 is mineral slide way oil CGLP.

RAVENOL Bettbahnöl 32 is characterized by good lubricating and sliding properties as well as high tackiness.

RAVENOL Bettbahnöl 32 is formulated with mineral base oils and contains additives and corrosion inhibitors to prevent rust formation and stains on slide ways and track surfaces.

RAVENOL Bettbahnöl 32 is compatible with most of drilling-, cutting or grinding emulsions. The lubricant film of the slide way oil is not washed off.

Application Notes

RAVENOL Bettbahnoel 32 can be used for all types of lubrication systems such as pressure, circulating or central lubrication. If necessary, it can be applied manually. It can also be used for lubricating bearings and gear boxes.

Characteristics

RAVENOL Bettbahnöl 32 offers:

- Very good stick-slip characteristics
- High tackiness
- Good corrosion protection, no rust and stain formation
- Resistance to aqueous metalworking fluids
- Good demulsification

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	854,0	EN ISO 12185
Colour		gelb	visual



Property	Unit	Data	Audit
Viscosity at 40°C	mm ² /s	5,7,9	DIN 51 562
Viscosity index VI		123	DIN ISO 2909
Pourpoint	°C	-33	DIN ISO 3016
Flash point (COC)	°C	216	DIN ISO 2592

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 20. January 2020