



RAVENOL DPS Fluid



FABRICATION SYNTHETIC

RECOMMENDATIONS HONDA DPSF2 ULTRA 4WD REAR | HONDA 08293-99904 | HONDA DPFII (DPSF) | HONDA 08200-9007

RAVENOL DPS Fluid is synthetic special fluid based on high-quality hydrocrack oils with special additives and inhibition which was developed for use in Dual Pump System (DPS) by Honda in the Service Fill area.

ART.-NR. 1211113

[Transla [Translate to
te to EnEnglisch:]
glisch:] |

[Transla [Translate to
te to EnEnglisch:]
glisch:] |

[Transla [Translate to
te to EnEnglisch:]
glisch:] |

[Transla [Translate to
te to EnEnglisch:]
glisch:] |

20 L | 1211113-B20

60 L | 1211113-060

60 L | 1211113-D60

208 L | 1211113-208

208 L | 1211113-D28

1000 L | 1211113-700

Application Notes

RAVENOL DPS Fluid is used in vehicles with 4WD Real Time, e.g. Honda CR-V, Honda Element, Honda Odyssey, Honda Fit, Honda Orthia and others.

Characteristics

RAVENOL DPS Fluid offers:

- Superior resistance to lubricant failure und hard operating conditions
- Very good lubricating properties even at low temperatures in winter
- High and stable viscosity index
- Oxidation resistance and thermal stability



- Extensive protection against wear, corrosion and foaming
- Good balanced coefficient of friction
- High thermal and oxidative stability
- An excellent cooling capacity.

RAVENOL special transmission fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the

product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult

our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to

malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission. Ravensberger

Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	838,0	EN ISO 12185
Colour		rot	visual
Pourpoint	°C	-54	DIN ISO 3016

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 15. December 2020