



## RAVENOL Feinmechaniköl



**RAVENOL Feinmechanik-Oel** is a multi-purpose, universal general purpose lubricant, resin- and acid-free and therefore particularly suitable for the lubrication of high technology precision mechanics.

**RAVENOL Feinmechanik-Oel** is dewaxed and treated in the hydrofinishing process and oxidizes itself only very slowly under UV and oxygen influence.

**RAVENOL Feinmechanik-Oel** is also suitable for very fast-acting mechanism.

**ART.-NR. 1350360**

100 ml | 1350360-100  
(VE 10  
Stück) |  
1 L | 1350360-001  
5 L | 1350360-005  
10 L | 1350360-010  
20 L | 1350360-020  
20 L | 1350360-B20  
1000 L | 1350360-700

## Application Notes

**RAVENOL Feinmechanik-Oel** can be used as a universal general purpose oil both in the home and out for bicycles, sewing machines, household and office equipment, locks, tools, cars, motorcycles, hobby work etc. and anywhere that this type of multi-purpose oil is required.

## Characteristics

**RAVENOL Feinmechanik-Oel** offers:

- Free from resin and acid, therefore no binding of deposits
- Low sulfur content
- Non-aging oil with a good viscosity-temperature behavior
- Good anticorrosive characteristics
- Very good wear reduction
- Easy handling and sprayability
- Wear protection and pressure absorption capacity



Property	Unit	Data	Audit
Colour		hell	visual
Density at 20°C	kg/m <sup>3</sup>	834,0	EN ISO 12185
Viscosity at 40°C	mm <sup>2</sup> /s	32,1	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	6,0	DIN 51562
Viscosity index VI		135	DIN ISO 2909
Pourpoint	°C	-18	DIN ISO 3016
Flash point (COC)	°C	190	DIN ISO 2592

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 16. August 2019