



## RAVENOL Fork Oil Heavy 15W



**VISCOSITY** 15W

**FABRICATION** MINERAL

**RECOMMENDATIONS** APRILIA | BMW | DUCATI | HONDA | KAWASAKI |  
MOTO-GUZZI | SUZUKI | TRIUMPH | YAMAHA

**RAVENOL Fork Oil Heavy 15W** is a fork oil on mineral oil base which was developed for all forks of off-road motorbikes and motor cross bikes.

**ART.-NR.** 1182105

1 L | 1182105-001

4 L | 1182105-004

**RAVENOL Fork Oil Heavy 15W** is especially characterised by a high and stable viscosity index as well as a solid corrosion protection. Efficient additives offer even under extreme loads an excellent corrosion protection. The behaviour against sealing materials is neutral.

## Application Notes

**RAVENOL Fork Oil Heavy 15W** was developed for the use in all chassis components of two-wheeler vehicles and offers good power characteristics. In order to obtain the optimum viscosity for the vehicle and operating condition the mineral fork oils are miscible among each other.

## Characteristics

**RAVENOL Fork Oil Heavy 15W** offers:

- good damping characteristics at all temperatures
- a high and stable viscosity index
- an excellent protection against corrosion, therefore a longer endurance of the fork components
- as far as possible protection against corrosion of the inside components
- a very good air and water separation behaviour to prevent foam formation
- neutral behaviour against sealings made of plastics
- a very low pour point

Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	860	EN ISO 12185
Colour		gelb	visual
Viscosity at 100°C	mm <sup>2</sup> /s	8,1	DIN 51 562
Viscosity at 40°C	mm <sup>2</sup> /s	46,0	DIN 51 562



Property	Unit	Data	Audit
Viscosity index VI	°C	<del>150</del>	DIN ISO 2909
Flash point (COC)	°C	208	DIN ISO 2592
TBN	mg KOH/g	0,4	ASTM D2896
Sulphated ash	%wt.	ca. 0,06	-
demulsifying power		40ml/40ml/10min.	-

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 17. March 2020