



RAVENOL Gasmotorenöl SAE 40



VISCOSITY 40
FABRICATION MINERAL

RAVENOL Gasmotorenöl SAE 40 is gas engine oil suitable for the lubrication of four stroke gas engines, when gases are used with lower sulphur contents.

ART.-NR. 1133105

20 L | 1133105-020
20 L | 1133105-B20
1000 L | 1133105-700

Application Notes

RAVENOL Gasmotorenöl SAE 40 is suitable to apply in four stroke gas engines for which lower acid neutralisation capacity is required.

RAVENOL Gasmotorenöl SAE 40 can be applied when natural gas, biomass gas or sewing gas are used. Application of this motor oil contributes to a longer lifetime and decreased maintenance costs, because longer service fill times are possible. Due to its lower phosphate content a longer lifetime of the catalyst can be achieved.

Characteristics

RAVENOL Gasmotorenöl SAE 40 offers:

- Reduction of deposits in the combustion chamber and on the valves
- Good noise reducing properties
- Good oxidation resistance
- Strong acid neutralisation capacity
- Excellent cleaning properties
- Good protection against wear
- Excellent filterability

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	872	EN ISO 12185
Colour		braun	visual



Property	Unit	Data	Audit
Viscosity at 100°C	mm ² /s	13,7	DIN 51 562
Viscosity at 40°C	mm ² /s	123,0	DIN 51 562
Viscosity index VI		108	DIN ISO 2909
Pourpoint	°C	- 21	DIN ISO 3016
Flash point (COC)	°C	274	DIN ISO 2592
TBN	mg KOH/g	5,5	ASTM D2896

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 03. December 2019