



RAVENOL Getriebeöl CLP 100



ART.-NR. 1332107

20L | 1332107-020

SPECIFICATIONS DIN 51 517 PART 3

RECOMMENDATIONS FZG 12 | AGMA 9005-D94 | CLEAN PANEL COKER | CINCINNATI MILACRON | S-200 OXIDATION TUBES | US STEEL 224

RAVENOL Getriebeöl CLP 100 is a high quality, mineral-based gear oil formulated with lead-free high-pressure additives (EP additives). Its special active substance combination provides a good, stable high-pressure impact load capacity.

RAVENOL Getriebeöl CLP 100 has a low pour point and therefore a very good cold behaviour.

RAVENOL Getriebeöl CLP 100 is free of zinc and ash due to its formulation.

Application Notes

RAVENOL Getriebeöl CLP 100 can be used as a lubricant in nearly all industrial gear drives due to its good stress and/or impact characteristics.

Characteristics

RAVENOL Getriebeöl CLP 100 offers:

- A very good, stable high-pressure impact capacity.
- Resistant characteristics at high temperatures.
- A good rust and corrosion impeding effect.
- Excellent wear protection.
- Very good anti-foaming characteristics.
- A low pour point.
- Very good cold behaviour

| Property | Unit | Data | Audit |
|--------------------|--------------------|-----------|--------------|
| Density at 20°C | kg/m ³ | 875,0 | EN ISO 12185 |
| Colour | | gelbbraun | visual |
| Viscosity at 100°C | mm ² /s | 11,4 | DIN 51 562 |
| Viscosity at 40°C | mm ² /s | 106,3 | DIN 51 562 |



| Property | Unit | Data | Audit |
|--------------------|------|------|--------------|
| Viscosity index VI | | 106 | DIN ISO 2909 |
| Pourpoint | °C | -21 | DIN ISO 3016 |
| Flash point | °C | 242 | DIN ISO 2592 |

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 20. January 2020