



RAVENOL Getriebeöl CLP 320



ART.-NR. 1332110

20L | 1332110-020

SPECIFICATIONS FZG 12 | VICKERS VANE PUMP | DIN 51 517 PART 3 | US STEEL 224 | EICKHOFF BERGBAUTECHNIK: BESTÄTIGUNG FÜR DIE VERWENDUNG IN DEN GETRIEBERÄUMEN

RECOMMENDATIONS US STEEL 224 | AGMA 9005-D94 | CINCINNATI MILACRON | CLEAN PANEL COKER | S-200 OXIDATION TUBES

RAVENOL Getriebeöl CLP 320 is high-grade industrial gear oil, based on mineral oil, formulated with lead-free EP-additives. Due to its special combination a very good, stable high-pressure absorption is achieved for shock load.

RAVENOL Getriebeöl CLP 320 has a low pour point and therefore very good low temperature properties.

RAVENOL Getriebeöl CLP 320 is free of zinc and ash due to its formulation.

Application Notes

RAVENOL Getriebeöl CLP 320 is to be used for the lubrication of almost any type of industrial gear box, even when exposed to heavy duty and shock loads.

Characteristics

RAVENOL Getriebeöl CLP 320 offers:

- a very good resistance towards high pressures and shock loads
- a good resistance against high temperatures
- good corrosion preventing properties
- an excellent prevention from wear
- a very good activity against foaming
- a low pour point

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	895	EN ISO 12185
Colour		gelbbraun	visual
Viscosity at 100°C	mm ² /s	24,3	DIN 51 562
Viscosity at 40°C	mm ² /s	327,6	DIN 51 562



Property	Unit	Data	Audit
Viscosity index VI	°C	95	DIN ISO 2900
Flash point (COC)	°C	244	DIN ISO 2592

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 20. January 2020