



RAVENOL Getriebeöl CLP 460



ART.-NR. 1332111

5 L | 1332111-005
20 L | 1332111-020
20 L | 1332111-B20
1000 L | 1332111-700

SPECIFICATIONS DIN 51 517 PART 3 | FZG 12 | US STEEL 224

RECOMMENDATIONS US STEEL 224 | AGMA 9005-D94 | CINCINNATI MILACRON | CLEAN PANEL COKER | S-200 OXIDATION TUBES

RAVENOL Getriebeöl CLP 460 is a high quality, mineral-based gear oil formulated with lead-free high-pressure additives (EP additives). Its special active substance combination provides a good, stable high-pressure impact load capacity.

RAVENOL Getriebeöl CLP 460 has a low pour point and therefore a good cold behaviour.

RAVENOL Getriebeöl CLP 460 is free of zinc and ash due to its formulation.

Application Notes

RAVENOL Getriebeöl CLP 460 can be used as a lubricant in nearly all industrial gear drives due to its good stress and/or impact characteristics.

Characteristics

RAVENOL Getriebeöl CLP 460 offers:

- A very good, stable high-pressure impact capacity.
- Resistant characteristics at high temperatures.
- A good rust and corrosion impeding effect.
- Excellent wear protection.
- Very good anti-foaming characteristics.
- A low pour point.
- Good cold behaviour

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	900	EN ISO 12185
Colour		gelbbraun	visual
Viscosity at 100°C	mm ² /s	31,2	DIN 51 562
Viscosity at 40°C	mm ² /s	490,3	DIN 51 562



Property	Unit	Data	Audit
Viscosity index VI		93	DIN ISO 2909
Pourpoint	°C	-12	DIN ISO 3016
Flash point (COC)	°C	224	DIN ISO 2592

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 20. January 2020