



RAVENOL Getriebeoel LS SAE 75W-90



VISCOSITY 75W-90

SPECIFICATIONS API GL-5 | MIL-L-2105 D | API GL-5 + LS (LIMITED SLIP)

FABRICATION SYNTHETIC

RECOMMENDATIONS ZF TE-ML 05C/D | GM 1940058 | GM 93165388 | GM 88862624 | GM 88862625

RAVENOL Getriebeoel LS SAE 75W-90 is a semi-synthetic lubricant for mechanical transmissions.

RAVENOL Getriebeoel LS SAE 75W-90 is designed based on high-quality solvent refined and synthetic base oils with special additive treatment and inhibition for higher stress on manual transmission oils and ensuring trouble-free transmission function.

ART.-NR. 1222102

1 L	1222102-001
4 L	1222102-004
10 L	1222102-010
20 L	1222102-020
20 L	1222102-B20
60 L	1222102-060
60 L	1222102-D60
208 L	1222102-208
208 L	1222102-D28
1000 L	1222102-700

Application Notes

RAVENOL Getriebeoel LS SAE 75W-90 was developed specifically for use in differential gear units with limited slip. It also ensures trouble-free lubrication in self-locking, hypoid geared transmissions.

Characteristics

RAVENOL LS SAE 75W-90 offers:

- excellent oxidation stability
- excellent protection against rust and corrosion
- prevents foaming
- outstanding extreme pressure properties
- excellent limited slip properties
- fuel savings



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	866,0	EN ISO 12185
Colour		hellgelb	visual
Viscosity at 100°C	mm ² /s	14,5	DIN 51562-10
Viscosity at 40°C	mm ² /s	81,5	DIN 51562-10
Viscosity index VI		188	DIN ISO 2909
Brookfield Viscosity	mPa*s	16.700	ASTM D 2983
Pourpoint	°C	-42	DIN ISO 3016
Flash point	°C	202	DIN ISO 2592
Copper Strip Test		1b	ASTM D130

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 30. July 2020