



RAVENOL MARINE Gear Lube



ART.-NR. 1233100

1 L | 1233100-001
 4 L | 1233100-004
 10 L | 1233100-010
 20 L | 1233100-020
 20 L | 1233100-B20
 60 L | 1233100-060
 60 L | 1233100-D60
 1000 L | 1233100-700

SPECIFICATIONS API GL-5
FABRICATION MINERAL
RECOMMENDATIONS OMC | MERCURISER | YANMAR

RAVENOL MARINE Gear Lube contains high-quality base oils, with a balanced combination of additives. This guarantees a high load carrying capacity, wear protection and oxidation stability.

Because of the balanced additive combination good viscosity-temperature behavior, low pour point and suppression of foam formation allows use with different operating conditions.

Application Notes

RAVENOL MARINE Gear Lube is gear oil for lubricating when GL-5 transmission types are required.

Characteristics

RAVENOL MARINE Gear Lube offers:

- Good adhesion and pressure-resistant lubricating film
- Excellent oxidation stability
- Very good viscosity-temperature behaviour
- Wear-resistant effect
- No foaming tendency
- A neutral behaviour towards metals and sealing materials

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	887,0	EN ISO 12185
Colour		blau	visual
Viscosity at 100°C	mm ² /s	14,1	DIN 51562-10
Viscosity at 40°C	mm ² /s	140,5	DIN 51562-10



Property	Unit	Data	Audit
Viscosity index VI		97	DIN ISO 2909
Pourpoint	°C	-33	DIN ISO 3016
Flash point (COC)	°C	212	DIN ISO 2592

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 03. December 2019