



## RAVENOL MARINE Power Trim & Steering Fluid



ART.-NR. 1234100

1 L | 1234100-001  
4 L | 1234100-004  
10 L | 1234100-010  
20 L | 1234100-020  
20 L | 1234100-B20  
1000 L | 1234100-700

FABRICATION MINERAL  
RECOMMENDATIONS OMC | MERCUISER | YANMAR

**RAVENOL MARINE Power Trim & Steering Fluid** is a high quality hydraulic oil based on specially selected solvent refined base oils.

It is particularly characterized by a high and stable viscosity index and reliable corrosion protection. Effective additives provide an excellent wear protection even under extreme loads. The behaviour towards sealing materials is neutral.

### Application Notes

**RAVENOL MARINE Power Trim & Steering Fluid** is an excellent product for lubrication of hydraulics in the marine area.

May not be used if in the hydraulic systems are silver and / or silver-plated construction and operating elements present.

### Characteristics

**RAVENOL MARINE Power Trim & Steering Fluid** offers:

- A high and stable viscosity index
- Excellent protection against wear
- Widest possible protection against corrosion
- A very good air and water separation to prevent foaming
- A neutral attitude towards plastic and seals
- A very low pour point



Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	851	EN ISO 12185
Colour		blau	visual
Viscosity at 100°C	mm <sup>2</sup> /s	6,3	DIN 51 562
Viscosity at 40°C	mm <sup>2</sup> /s	32,0	DIN 51 562
Viscosity index VI		152	DIN ISO 2909
Pourpoint	°C	-39	DIN ISO 3016
Flash point (COC)	°C	215	DIN ISO 2592
TBN	mg KOH/g	0,4	ASTM D2896
Sulphated ash	%wt.	0,06	DIN 51 575

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 03. December 2019