



## RAVENOL MARINEOIL PETROL 20W-50



**VISCOSITY** 20W-50  
**SPECIFICATIONS** API SL  
**FABRICATION** MINERAL  
**RECOMMENDATIONS** YANMAR | MERCUISER | VOLVO PENTA AB | KOHLER

**RAVENOL MARINEOIL PETROL 20W-50** is a multi-range engine oil for marine gasoline engines.

**RAVENOL MARINEOIL PETROL 20W-50** corresponds to the demands of the SAE class 20W-50. This viscosity classification guarantees a good lubricating film also under complicate operating conditions.

**ART.-NR. 1163210**

4 L | 1163210-004  
 10 L | 1163210-010  
 20 L | 1163210-020  
 20 L | 1163210-B20  
 1000 L | 1163210-700

## Characteristics

**RAVENOL MARINEOIL PETROL 20W-50** offers :

- an extreme high pressure absorption capacity
- a very high oxidation stability
- an excellent aging resistance
- an excellent viscosity temperature behaviour
- high safety reserves also under boundary lubrication conditions
- suitability for extended oil change intervals
- suitability for complicate operating conditions
- a good water separation behaviour

Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	881,0	EN ISO 12185
Colour		blau	visual
Viscosity at 100°C	mm <sup>2</sup> /s	18,5	DIN 51 562
Viscosity at 40°C	mm <sup>2</sup> /s	161,0	DIN 51 562



Property	Unit	Data	Audit
Viscosity index VI	°C	<del>130</del>	DIN ISO 2909
Flash point (COC)	°C	247	DIN ISO 2592
TBN	mg KOH/g	10,7	ASTM D2896
Sulphated ash	%wt.	1,42	DIN 51757

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 14. June 2019