



RAVENOL MARINEOIL PETROL SAE 10W-40



VISCOSITY 10W-40

SPECIFICATIONS API SL

RECOMMENDATIONS MERCUISER | YANMAR | VOLVO PENTA AB | KOHLER

RAVENOL MARINEOIL PETROL SAE 10W-40 is an engine oil for the use in marine gasoline engines.

ART.-NR. 1162200

1 L | 1162200-001
4 L | 1162200-004
10 L | 1162200-010
20 L | 1162200-020
20 L | 1162200-B20
60 L | 1162200-060
60 L | 1162200-D60
1000 L | 1162200-700

RAVENOL MARINEOIL PETROL SAE 10W-40 is produced with unconventional and HC basic oils, synthetic components and modern additives.

RAVENOL MARINEOIL PETROL SAE 10W-40 guarantees longest oil change intervals and a high corrosion protection with a low oil and fuel consumption.

Characteristics

RAVENOL MARINEOIL PETROL SAE 10W-40 offers:

- excellent detergent and dispersant characteristics
- low evaporation
- high aging stability
- protection of reflecting surface formation
- very good cold start characteristics
- reduces oil and fuel consumption

| Property | Unit | Data | Audit |
|--------------------|--------------------|-------|--------------|
| Density at 20°C | kg/m ³ | 866,0 | EN ISO 12185 |
| Colour | | blau | visual |
| Viscosity at 100°C | mm ² /s | 13,7 | DIN 51 562 |
| Viscosity at 40°C | mm ² /s | 92,0 | DIN 51 562 |



| Property | Unit | Data | Audit |
|--------------------|----------|-------|--------------|
| Viscosity at -25°C | mPa.s | <7000 | ASTM D5293 |
| Viscosity index VI | | 151 | DIN ISO 2909 |
| Pourpoint | °C | -36 | DIN ISO 3016 |
| Flash point (COC) | °C | 214 | DIN ISO 2592 |
| TBN | mg KOH/g | 11 | ASTM D2896 |
| Sulphated ash | %wt. | 1,3 | - |

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 14. June 2019