



## RAVENOL MARINEOIL PETROL SAE 15W-40



ART.-NR. 1163200

1 L | 1163200-001  
4 L | 1163200-004  
10 L | 1163200-010  
20 L | 1163200-020  
20 L | 1163200-B20  
1000 L | 1163200-700

**VISCOSITY** 15W-40

**SPECIFICATIONS** API SL

**FABRICATION** MINERAL

**RECOMMENDATIONS** VOLVO PENTA AB | MERCUISER | YANMAR | KOHLER

**RAVENOL MARINEOIL PETROL SAE 15W-40** is a high additive treated HD engine oil for marine gasoline engines.

**RAVENOL MARINEOIL PETROL SAE 15W-40** is especially produced for extended oil change intervals (under consideration of the manufacturer instruction).

## Characteristics

**RAVENOL MARINEOIL PETROL 15W-40** offers :

- an extreme high pressure absorption capacity
- a very high oxidation stability
- an excellent aging resistance
- an excellent viscosity temperature behaviour
- high safety reserves also under boundary lubrication conditions
- suitability for extended oil change intervals
- suitability for complicate operating conditions

Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	871	EN ISO 12185
Colour		blau	visual
Viscosity at 100°C	mm <sup>2</sup> /s	14,1	DIN 51 562
Viscosity at 40°C	mm <sup>2</sup> /s	101,0	DIN 51 562



Property	Unit	Data	Audit
Viscosity index VI	°C	<del>130</del>	DIN ISO 2900
Flash point (COC)	°C	236	DIN ISO 2592
TBN	mg KOH/g	10,1	ASTM D2896

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 14. June 2019