



## RAVENOL MARINEOIL PETROL SAE 25W-40 SYNTHETIC



ART.-NR. 1162115

4 L | 1162115-004  
10 L | 1162115-010  
20 L | 1162115-020  
20 L | 1162115-B20  
1000 L | 1162115-700

**VISCOSITY** 25W-40

**SPECIFICATIONS** API SL | ACEA A3/B4

**FABRICATION** FULLY SYNTHETIC

**RECOMMENDATIONS** VETUS DEUTZ | STEYR | MTU | VOLVO | MAN |  
MERCUISER | PERKINS | NANNI DIESEL | YANMAR | DETROIT DIESEL |  
SULZER | SKL

**RAVENOL MARINEOIL PETROL 25W-40 synthetic** is an engine oil for the use in marine petrol engines.

**RAVENOL MARINEOIL PETROL 25W-40 synthetic** is produced with unconventional and HC basic oils, synthetic components and additives.

**RAVENOL MARINEOIL PETROL 25W-40 synthetic** guarantees longest oil change intervals and a high corrosion protection with a low oil and fuel consumption.

## Characteristics

**RAVENOL MARINEOIL PETROL 25W-40 synthetic** offers :

- excellent detergent and dispersant characteristics
- low evaporation
- high aging stability
- protection of reflecting surface formation
- very good cold start characteristics
- reduces oil and fuel consumption

Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	866,0	DIN 51 757
Colour		blau	visual
Viscosity at 100°C	mm <sup>2</sup> /s	13,7	DIN 51 562
Viscosity at 40°C	mm <sup>2</sup> /s	92,0	DIN 51 562
Viscosity at -25°C	mPa.s	<7000	DIN 51 377
Viscosity index VI		151	DIN ISO 2909



Property	Unit	Data	Audit
Pourpoint	°C	- 36	DIN ISO 3016
Flash point (COC)	°C	214	DIN ISO 2592
TBN	mg KOH/g	11	ASTM D2896
Sulphated ash	%wt.	1,3	-

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 14. June 2019