



## RAVENOL MARINEOIL SHPD 25W-40 synthetic



ART.-NR. 1162105

1 L | 1162105-001  
4 L | 1162105-004  
10 L | 1162105-010  
20 L | 1162105-020  
20 L | 1162105-B20  
1000 L | 1162105-700

**VISCOSITY** 25W-40

**SPECIFICATIONS** ACEA B4 | ACEA E7 | API CF | API CI-4

**FABRICATION** FULLY SYNTHETIC

**RECOMMENDATIONS** DETROIT DIESEL | CATERPILLAR | STEYR | NANNI DIESEL | SKL | MAN | PERKINS | SULZER | VETUS DEUTZ | YANMAR | IVECO | MTU | MERCUISER

**RAVENOL MARINEOIL SHPD 25W-40 synthetic** is an engine oil for the use in marine diesel engines.

**RAVENOL MARINEOIL SHPD 25W-40 synthetic** is produced with unconventional and HC basic oils, synthetic components and modern additives.

**RAVENOL MARINEOIL SHPD 25W-40 synthetic** guarantees longest oil change intervals and a high corrosion protection with a low oil and fuel consumption.

## Characteristics

**RAVENOL MARINEOIL SHPD 25W-40 synthetic** offers:

- excellent detergent and dispersant characteristics
- low evaporation
- high aging stability
- protection of reflecting surface formation
- very good cold start characteristics
- reduces oil and fuel consumption

Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	866,0	EN ISO 12185
Viscosity at 100°C	mm <sup>2</sup> /s	13,7	DIN 51 562
Viscosity at -25°C	mPa.s	<7000	ASTM D5293
Viscosity at 40°C	mm <sup>2</sup> /s	92,0	DIN 51 562



Property	Unit	Data	Audit
Viscosity index VI		151	DIN ISO 2909
Pourpoint	°C	-36	DIN ISO 3016
Flash point (COC)	°C	214	DIN ISO 2592
TBN	mg KOH/g	11	ASTM D2896
Sulphated ash	%wt.	1,3	-

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 14. June 2019