



RAVENOL Mehrzweckfett OML



ART.-NR. 1340101

1 kg | 1340101-001
5 kg | 1340101-005
10 kg | 1340101-010
15 kg | 1340101-015
25 kg | 1340101-025
100 g | 1340101-100
180 kg | 1340101-180
200 g | 1340101-200
400 g | 1340101-400

SPECIFICATIONS DIN 51 502: K2K-30, ISO 6743 PART 9: ISO-L-XCCEA2
APPROVALS MB-APPROVAL 267.0

RAVENOL Mehrzweckfett OML is a lithium saponified multipurpose grease with oxidation and corrosion protective additives.

RAVENOL Mehrzweckfett OML has an extreme mechanical stability and a very low friction value. Therefore it can be transported easily.

Application Notes

RAVENOL Mehrzweckfett OML is used for the lubrication of easy loaded antifriction bearings and machine components. It is also suited as a multipurpose lubrication grease for vehicles.

Characteristics

RAVENOL Mehrzweckfett OML offers:

- universal use, multipurpose characteristic for a mixed car pool
- an extreme shear stability
- an excellent corrosion protection
- a very good mechanical and chemical stability
- a very good aging resistant
- a good pump output also at low temperatures



Property	Unit	Data	Audit
Colour		hellbraun	visual
Thickener		Lithium-Komplexseifen	-
NLGI-Class		2	DIN 51 818
DIN-Product-Classification		K2K-30	DIN 51 502
ISO-Product-Classification		ISO-L-XCCEA2	ISO 6743 P.9
Working Temperature	°C	-30 / +120	DIN 51 825
Short Term up to	°C	130	-
Worked Penetration 60 strokes	mm/10 bei 25°C	265-295	ISO 2137
Corrosion (SKF Emscor dist. Water)	Corr. Degree	1	DIN 51 802
Dropping Point	°C	>180	DIN ISO 2176
Water Resistance (3h/90°C)	°C	1-90	DIN 51 807 T.1
VKA Pressure Carrying Capacity	N	2000 bis 2200	DIN 51 350 T.4
Kinematic Viscosity (Base Oil)	mm ² /s bei 40°C	130	DIN 51562-1

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 12. January 2015