



RAVENOL MM SP-III Fluid



ART.-NR. 1212103

1 L	1212103-001
4 L	1212103-004
10 L	1212103-010
20 L	1212103-020
20 L	1212103-B20
60 L	1212103-060
60 L	1212103-D60
208 L	1212103-208
208 L	1212103-D28
1000 L	1212103-700

FABRICATION SYNTHETIC

RECOMMENDATIONS MITSUBISHI 4024401 | MITSUBISHI 4024610 | MITSUBISHI ACH1ZC1X05 | MITSUBISHI MZ320159 | MITSUBISHI MZ320162 | MITSUBISHI ATF SP-III | MITSUBISHI ATF SP-3 | HYUNDAI 04500-00100 | HYUNDAI 04500-00400 | HYUNDAI 04500-00A00 | HYUNDAI 00232-19052

RAVENOL ATF MM SP-III Fluid is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

RAVENOL ATF MM SP-III Fluid is universal ATF (Automatic Transmission Fluid) for automatic transmission of Mitsubishi, Hyundai and KIA.

RAVENOL ATF MM SP-III Fluid guarantees maximum wear protection in all operating conditions.

Application Notes

RAVENOL ATF MM SP-III Fluid was developed for use in automatic transmission, especially for Mitsubishi, Hyundai and KIA.

RAVENOL ATF MM SP-III Fluid can replace SP und SP-II Fluids.

It is advisable to flush with **RAVENOL ATF MM SP-III Fluid** before filling with **RAVENOL ATF MM SP-III Fluid**.

Characteristics

RAVENOL ATF MM SP-III Fluid offers:

- Very good lubricating properties also at low temperatures in winter
- High, stable viscosity index
- Very low pour point
- Excellent oxidation stability
- Protection against wear, corrosion and foaming
- Good concerted friction characteristic
- Neutral behavior towards sealing materials



- Neutral behavior by inhibition to non-ferrous metals

RAVENOL special transmission fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult

our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to

malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission. Ravensberger

Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	847,0	EN ISO 12185
Colour		rot	visual
Pourpoint	°C	-48	DIN ISO 3016

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 21. August 2019