



RAVENOL Motogear SAE 10W-30 GL-4



ART.-NR. 1250100

1 L | 1250100-001
4 L | 1250100-004

VISCOSITY 10W-30
SPECIFICATIONS API GL-4 | SAE 10W-30
FABRICATION SEMI-SYNTHETIC
RECOMMENDATIONS YAMAHA

RAVENOL MOTOGEAR SAE 10W-30 GL-4 is a semi-synthetic special multi-grade transmission fluid which is specially formulated for air and water cooled 2 and 4-stroke engines with separate gearbox lubrication.

RAVENOL MOTOGEAR SAE 10W-30 GL-4 has an excellent lubricating film adhesion, excellent detergency and high resistance to aging.

RAVENOL MOTOGEAR SAE 10W-30 GL-4 enables a precise and soft changing of gears. Prevents clutch slippage.

RAVENOL MOTOGEAR SAE 10W-30 GL-4 forms a heavy-duty lubricant film, which is effective under all operating conditions.

Application Notes

RAVENOL MOTOGEAR SAE 10W-30 GL-4 is designed for year-round use in all modern motorcycles of Japanese manufacturer's as YAMAHA.

Characteristics

RAVENOL MOTOGEAR SAE 10W-30 GL-4 offers:

- Quick lubrication of the engine at all operating temperatures.
- Heavy-duty lubricant film under all operating conditions.
- Precise, soft changing of gears, no clutch slippage.
- Reliability due to excellent lubricant film adhesion, extraordinary purification capacity and outstanding ageing resistance.
- Neutral towards sealing compounds.

| Property | Unit | Data | Audit |
|--------------------|--------------------|-----------|--------------|
| Density at 20°C | kg/m ³ | 858 | EN ISO 12185 |
| Colour | | gelbbraun | visual |
| Viscosity at 100°C | mm ² /s | 10,2 | DIN 51 562 |
| Viscosity at 40°C | mm ² /s | 64,3 | DIN 51 562 |



| Property | Unit | Data | Audit |
|--------------------|----------|------|--------------|
| Viscosity index VI | | 145 | DIN ISO 2909 |
| Pourpoint | °C | -33 | DIN ISO 3016 |
| Flash point (COC) | °C | 232 | DIN ISO 2592 |
| TBN | mg KOH/g | 8,6 | ASTM D2896 |

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 30. October 2019