



RAVENOL MTF-2 SAE 75W-80



ART.-NR. 1221103

1 L	1221103-001
4 L	1221103-004
10 L	1221103-010
20 L	1221103-020
20 L	1221103-B20
60 L	1221103-060
60 L	1221103-D60
208 L	1221103-208
208 L	1221103-D28
1000 L	1221103-700

VISCOSITY 75W-80

SPECIFICATIONS API GL-4 |MT-1

FABRICATION FULLY SYNTHETIC

RECOMMENDATIONS AC DELCO 10-4033 | GENERAL MOTORS 1940711 | GENERAL MOTORS 88861801 | BMW 2300 7533 513 MTF LT-2 | BMW 2300 7533 818 MTF LT-3 | BMW 83 22 0 309 031 2300 1434 404 MTF LT-1 | FIAT 9.55550-MZ2 F178.B06 14621616 | FORD WSS-M2C200-D2 WSS-M2C200-C3 1547953 1382914 | GENERAL MOTORS 88861800 | HONDA 08261-99964 GENUINE MTF FLUID 08798-9031 | HYUNDAI 02200-00130 TOD | LAND ROVER STC 9157 TYK500030 STC 9158 | MB 235.10 | MITSUBISHI MZ312644 3005401 | MTF-94 FLUID FÜR LAND ROVER | MG AND MINI COOPER | NISSAN 999MP-MTF20P KE91699932R | PEUGEOT 9730A2 | SUBARU K0321-F0090 | TOYOTA 08885-00705 | VOLVO 1161681 1161745 | VW/AUDI G 052911A2 G 055538A2 FÜR ZF 6S450 AMAROK 0C6 | MTF XT4447 M+ | MTF ETL8997B | MTF 97309 | PSA B71 2330 | AUDI G 052 532 UND G 055 532

RAVENOL MTF-2 SAE 75W-80 is a PAO based fully synthetic low-viscosity transmission oil for modern manual transmission.

RAVENOL MTF-2 SAE 75W-80 is designed based on synthetic base oils and specially coordinated additive treatment. This exceeds the needs of today's application requirements.

RAVENOL MTF-2 SAE 75W-85 is outstanding for use under severe mechanical and thermal stress on transmission oils, even with extended oil change intervals.

Application Notes

RAVENOL MTF-2 SAE 75W-80 is a fully synthetic transmission oil for manual transmissions.

Characteristics

RAVENOL MTF-2 SAE 75W-80 offers:

- A high-pressure stable lubricating film even at high oil temperatures and under high stress.
- Outstanding shearing stability and excellent thermal stability.
- Excellent viscosity-temperature properties.
- High oxidation stability.
- Excellent wear protection, outstanding EP properties.
- Low foaming property even at high speeds.
- Good shifting behaviour even in low temperatures, extremely low pour point.



- Extended life.

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	844,0	EN ISO 12185
Colour		gelbbraun	visual
Brookfield Viscosity	mPa*s	18.800	ASTM D 2983
Pourpoint	°C	-51	DIN ISO 3016
Copper Strip Test		1a	ASTM D130

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 10. March 2020