



## RAVENOL MTF-3 SAE 75W



ART.-NR. 1221104

1 L | 1221104-001  
4 L | 1221104-004  
10 L | 1221104-010  
20 L | 1221104-020  
20 L | 1221104-B20  
60 L | 1221104-060  
60 L | 1221104-D60  
208 L | 1221104-208  
208 L | 1221104-D28  
1000 L | 1221104-700

**VISCOSITY** 75W

**FABRICATION** FULLY SYNTHETIC

**RECOMMENDATIONS** FORD WSS-M2C200-D3 | AC DELCO 10-4037 | VW G 070 726 A2 | GM 1940004 | GM 19259104 | FIAT 9.55550-MZ6 | BOT 350 M3 | BOT 350 M3 | FORD WSS-M2C200-D2 | MTF JWS2271 | MERCEDES A001989840309 | MB 235.10 | OPEL B0402167 | PSA STANDARD 9730A8 | TOYOTA 08885-81001 | TOYOTA 08885-8081 | SUZUKI 99000-22B27-036 | VW G 055 532 A2 | VW G 052 527 A2 | VW G 052 171 A2 | VW G 052 527 | VW G 052 512 A2 | VW G 009 317 A2 | VW/AUDI G 060 726 A2 | VOLVO 1161839 | VOLVO 1161838 | BMW MTF LT-3 23 00 7 533 818, 83 22 0 396 706, 83 22 7 533 818 | JWS2271

**RAVENOL MTF-3 SAE 75W** is a fully synthetic low-viscosity transmission oil for special manual transmissions.

**RAVENOL MTF-3 SAE 75W** is designed based on special selected base oils and specially coordinated additive treatment. This exceeds the needs of today's application requirements.

**RAVENOL MTF-3 SAE 75W** is outstanding for use under severe mechanical and thermal stress on transmission oils, even with extended oil change intervals.

## Application Notes

**RAVENOL MTF-3 SAE 75W** is a fully synthetic transmission oil for manual transmissions.

## Characteristics

**RAVENOL MTF-3 SAE 75W** offers:

- A high pressure stable lubricating film even at high oil temperatures and under high stress.
- Outstanding shearing stability and excellent thermal stability.
- Excellent viscosity-temperature properties.
- High oxidation stability.
- Excellent wear protection, outstanding EP properties.
- Low foaming properties even at high speeds.
- Good shifting behaviour even in low temperatures, extremely low pour point.
- Extended life.
- A stable lubricating film even at high oil temperatures and under high stress.



RAVENOL special transmission fluid is special development for special gear and can not be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult

our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to

malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission. Ravensberger

Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.



Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	844,0	EN ISO 12185
Colour		gelbbraun	visual
Brookfield Viscosity	mPa*s	11.000	ASTM D 2983
Pourpoint	°C	-51	DIN ISO 3016
Copper Strip Test		1b	ASTM D130

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 14. October 2020