



RAVENOL Outboardoel 2T Fullsynth.



ART.-NR. 1151200

1 L | 1151200-001
4 L | 1151200-004
5 L | 1151200-005
10 L | 1151200-010
20 L | 1151200-020
20 L | 1151200-B20
1000 L | 1151200-700

SPECIFICATIONS API TD
FABRICATION FULLY SYNTHETIC
APPROVALS NMMA TC-W3® | RL-90001G

RAVENOL Outboardoel 2T Fullsynth. is high performance 2-stroke engine oil based on polyolesters with special esters and Polyisobutylene (PIB) and with an ash less additive package for optimum lubricity and excellent corrosion protection.

RAVENOL Outboardoel 2T Fullsynth. is especially designed for outboard engines with or without Direct Fuel Injection (DFI) Systems in fresh water cooled outboard engines with separate (Auto lube systems) or mixed lubrication.

RAVENOL Outboardoel 2T Fullsynth. meets the requirements of the National Marine Manufacturers Association NMMA TC-W3 (Yamaha CE 50S, Mercury).

Application Notes

RAVENOL Outboardoel 2T Fullsynth. is recommended for "TC-W3" Fluids in all outboard engines according to the prescribed mixing ratio from the engine manufacturer. It can also be used for engines operating in seawater.

RAVENOL Outboardoel 2T Fullsynth. is recommended for use in 2-stroke outboard engines with or without Direct Fuel Injection (DFI) Systems. For example OptiMax (Mercury), E-TEC (BRP: Evinrude and Johnson), HPDI (Yamaha), TLDI (Tohatsu, Nissan Marine), DFI (Selva).

Typical mixing ratio: 1:100
Follow the manufacturers recommendations!

Characteristics

RAVENOL Outboardoel 2T Fullsynth. offers:

- An excellent corrosion protection in all oil-wetted engine parts
- Immediate, homogeneous mixture with the used fuel (including lead-free)
- An effective pressure and temperature resistant oil film
- An excellent anti-wear performance
- A clean burning with no deposits
- An excellent anti-wear performance
- Low coking



- High wear protection

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	864,0	EN ISO 12185
Colour		blau	visual
Viscosity at 100°C	mm ² /s	10,7	DIN 51 562
Viscosity at 40°C	mm ² /s	70,8	DIN 51 562
Viscosity index VI		143	DIN ISO 2909
Pourpoint	°C	-48	DIN ISO 3016
Flash point (COC)	°C	143	DIN ISO 2592

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 03. December 2019