



RAVENOL Schneefräse 4-Takt 5W-30



VISCOSITY 5W-30

SPECIFICATIONS API SM | API SL | ACEA A5/B5

FABRICATION FULLY SYNTHETIC

RECOMMENDATIONS MTD | HONDA | TORO | YARD-MAN | CUBCADET | BRIGGS&STRATTON | MCCULLOCH | CRAFTSMAN | MURRAY | ARIENS | CAIMAN | CANADIANA | HUSQVARNA | PARTNER | SNAPPER | STIGA | SWISHER | WHITE OUTDOOR

ART.-NR. 1151105

1 L | 1151105-001

4 L | 1151105-004

RAVENOL Schneefräse 4-Takt SAE 5W-30 is high quality fully synthetic green coloured four-stroke engine oil. It is specially designed for 4-stroke snow blowers. Excellent wear protection also by high pressure, excellent corrosion protection. Because of the noticeable fuel economy **RAVENOL Schneefräse 4-Takt SAE 5W-30** contributes to the reduction of pollutant emissions and protecting the environment.

Application Notes

RAVENOL Schneefräse 4-Takt SAE 5W-30 is fuel efficient engine oil special conceived for 4-stroke snow blower engines.

Characteristics

RAVENOL Schneefräse 4-Takt SAE 5W-30 offers:

- Fast oiling of the engine, also by low temperatures
- Low oil consumption because of the low evaporation tendency
- Excellent wear protection by high pressure
- Excellent corrosion protection
- Safety towards sludge, coking, leaking and corrosion also in unfavourable operational conditions
- No oil caused deposits in combustion chambers, in piston ring zone and on valves.
- Neutrality against seal materials

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	842,0	EN ISO 12185
Colour		grün	visual
Viscosity at 100°C	mm ² /s	9,6	DIN 51 562
Viscosity at 40°C	mm ² /s	53,3	DIN 51 562



Property	Unit	Data	Audit
Viscosity index VI		167	DIN ISO 2909
CCS Viscosity at -30°C	mPa*s	3460	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -35°C	mPa*s	16.500	ASTM D 4684
Pourpoint	°C	-36	DIN ISO 3016
Noack Volatility	% M/M	7,9	ASTM D5800/b
Flash point (COC)	°C	236	DIN ISO 2592
TBN	mg KOH/g	11,4	ASTM D2896
Sulphated ash	%wt.	1,1	DIN 51 575

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 04. December 2019