



## RAVENOL SCOOTER 2-Takt Fullsynth.



ART.-NR. 1151150

1 L | 1151150-001  
4 L | 1151150-004  
10 L | 1151150-010  
20 L | 1151150-020  
20 L | 1151150-B20  
10000 L 1151150-700

**SPECIFICATIONS** API TD | ISO-L-EGD

**FABRICATION** FULLY SYNTHETIC

**APPROVALS** JASO FD (049RAV153)

**RECOMMENDATIONS** APRILIA | HONDA | KYMCO | PEUGEOT | PIAGGIO | SUZUKI | VESPA | YAMAHA

**RAVENOL SCOOTER 2-Takt Fullsynth.** is high quality fully synthetic two-stroke engine oil.

**RAVENOL SCOOTER 2-Takt Fullsynth.** is based on Polyolester with special esters and Polyisobutylene (PIB) for optimum protection against wear and prevent corrosion, deposits and auto-ignitions, even with heavy loads.

**RAVENOL SCOOTER 2-Takt Fullsynth.** is optimized for air- and watercooled two stroke engines in Scooters.

## Application Notes

**RAVENOL SCOOTER 2-Takt Fullsynth.** can generally be mixed with regular petrol 1:100.

**RAVENOL SCOOTER 2-Takt Fullsynth.** is best choice for air- and watercooled two stroke engines in Scooters.

**RAVENOL SCOOTER 2-Takt Fullsynth.** is used for lubrication of air-cooled two-stroke petrol engines with very high speed and heaviest load.

**RAVENOL SCOOTER 2-Takt Fullsynth.** is also suitable for the lubrication of two stroke scooters with water cooling. Suitable for separate lubrication systems and self-mixing systems.

## Characteristics

**RAVENOL SCOOTER 2-Takt Fullsynth.** offers:

- A proper lubrication of all engine parts
- A strong cleaning effect, for clean combustion chambers. Cleans intake and exhaust ports from combustion residues and deposits
- Clean spark plugs provide optimal performance of the engines
- A very high wear and corrosion protection
- Low exhaust emission levels by good combustion
- Very low Pourpoint, also to use at very low temperature



Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	864,0	EN ISO 12185
Colour		rot	visual
Viscosity at 100°C	mm <sup>2</sup> /s	10,8	DIN 51 562
Viscosity at 40°C	mm <sup>2</sup> /s	70,7	DIN 51 562
Viscosity index VI		142	DIN ISO 2909
Pourpoint	°C	-45	DIN ISO 3016
Flash point (COC)	°C	142	DIN ISO 2592

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 15. September 2020