



## RAVENOL Standard Truck SAE 30



ART.-NR. 1123620

20 L | 1123620-020  
20 L | 1123620-B20  
1000 L | 1123620-700

**VISCOSITY** 30

**SPECIFICATIONS** API CF | API SF

**FABRICATION** MINERAL

**RECOMMENDATIONS** MTU TYP 1 (DDC BR 2000 AND 4000) | MB 227.0 | CATERPILLAR TO-2 | ALLISON C4 | MIL-L-2104 E | MAN 270 | VOITH RETARDER A | VOITH DIWA, ZF TE-ML 02C, 03B, 04B, 06A, 07D

**RAVENOL Standard Truck SAE 30** is mineral mono grade motor oil for trucks. All-season oil for all truck diesel engine types. High protection against friction and abrasion, excellent cold start characteristics. Extended oil change intervals according to manufacturer's recommendations.

## Application Notes

**RAVENOL Standard Truck SAE 30** is mono grade motor oil for use in truck diesel engines. Also suitable for stationary plants.

## Characteristics

**RAVENOL Standard Truck SAE 30** offers:

- Good shear stability
- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety reserves
- Good cold start characteristics
- Best corrosion protection
- Suitable for catalysts

Property	Unit	Data	Audit
Colour		gelbbraun	visual
Density at 20°C	kg/m <sup>3</sup>	887,0	EN ISO 12185
Viscosity at 40°C	mm <sup>2</sup> /s	102,3	DIN 51 562



Property	Unit	Data	Audit
Viscosity at 100°C	mm <sup>2</sup> /s	100	DIN ISO 2909
Pourpoint	°C	-27	DIN ISO 3016
Flash point (COC)	°C	262	DIN ISO 2592
TBN	mg KOH/g	13,0	ASTM D2896

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 03. December 2019