



RAVENOL STOU SAE 10W-40



ART.-NR. 1310111

10 L | 1310111-010
20 L | 1310111-020
20 L | 1310111-B20
1000 L | 1310111-700

VISCOSITY 10W-40

SPECIFICATIONS API GL-4 | API CG-4 | API SF | ACEA E3

FABRICATION SEMI-SYNTHETIC

RECOMMENDATIONS MOTORENÖL: | NEW HOLLAND NH 410B, FORD ESN-M2C-134 B/C/D, FORD ESN-M2C-159B/C | GETRIEBEÖL: | SAE 80W, 85W, 80W-90, 85W-90, API GL-4, ALLISON C-4, CATERPILLAR TO-2 | HYDRAULIKÖL: | HVLP ISO VG 68-100 | SPEZIALTRAKTORENÖL: | JOHN DEERE J20C/D, J27, MASSEY-FERGUSON M1139, M1144, M1145 | CASE IH-MS 1209, FENDT KDM 41.2011, MAT 3525 | KOMPRESSORENÖL: | HOLMAN COMPAIR KOMPRESSOR, ATLAS COPCO KOMPRESSOR

RAVENOL STOU SAE 10W-40 is an up-to-date multifunctional lubricating oil for agricultural machinery, excavators and construction machinery and is formulated with top-grade solvent refined base oils and additives.

RAVENOL STOU SAE 10W-40 meets the recommendations of all well known tractor manufacturers and is equal to use in engines, transmissions and hydraulic systems of modern tractors. Ensures trouble-free operation of all units in all seasons.

Application Notes

RAVENOL STOU SAE 10W-40 has a wide range of applications in engines, transmissions and hydraulic systems of modern tractors.

RAVENOL STOU SAE 10W-40 is suitable as an engine oil for gasoline engines and intake and turbo charged diesel engines, also as gear oil (including wet brakes) and as hydraulic oil.

Characteristics

RAVENOL STOU SAE 10W-40 offers:

- A powerful dispersion and detergency
- A high activity against wear, corrosion and foam
- A very strong resistance to oxidation
- A high and stable viscosity index
- An excellent extreme pressure properties



| Property | Unit | Data | Audit |
|--------------------|--------------------|-----------|--------------|
| Colour | | gelbbraun | visual |
| Density at 20°C | kg/m ³ | 867 | EN ISO 12185 |
| Viscosity at -25°C | mPa.s | 5278 | ASTM D5293 |
| Viscosity at 40°C | mm ² /s | 84,2 | DIN 51 562 |
| Viscosity at 100°C | mm ² /s | 12,8 | DIN 51 562 |
| Viscosity index VI | | 151 | DIN ISO 2909 |
| Pourpoint | °C | -33 | DIN ISO 3016 |
| Flash point (COC) | °C | 234 | DIN ISO 2592 |
| TBN | mg KOH/g | 12,4 | ASTM D2896 |
| Sulphated ash | %wt. | 1,45 | DIN 51 575 |

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 03. December 2019