



RAVENOL STOU SAE 15W-40



VISCOSITY 15W-40

SPECIFICATIONS API SF | API CE | API CF-4 | API GL-4 | ACEA E1 | CCMC D4 | CCMC G2

FABRICATION MINERAL

RECOMMENDATIONS ZF TE-ML 06B | ZF TE-ML 07B | ALLISON C-4 | CATERPILLAR TO-2 | FORD M2C-159C | FORD M2C-86A | FORD M2C-134D | MF M-1143/1144 | MB 227.1 | JOHN DEERE J 27 | NH 420A | NH 410B

ART.-NR. 1310113

5 L | 1310113-005
20 L | 1310113-020
20 L | 1310113-B20
1000 L | 1310113-700

RAVENOL STOU SAE 15W-40 is a multi-purpose super universal tractor oil for agricultural machinery, excavators and construction equipment made from specially selected solvent-refined base oils. It is formulated to meet the requirements of all major tractor manufacturers as listed below, and can be used in engines, transmissions and hydraulic systems of most equipment in all seasons which require this grade of oil.

Application Notes

RAVENOL STOU SAE 15W-40 has a wide range of applications in engines, transmissions and hydraulic systems of many tractors and is suitable for use as motor oil for both petrol and diesel engines, transmission oil (including wet brakes and PTO transmissions) and as a hydraulic oil where this specification of product is required. Can also be used as compressor oil.

Characteristics

RAVENOL STOU SAE 15W-40 offers:

- Excellent viscosity-temperature behaviour
- Exceptional cold starting abilities
- Excellent detergent and dispersant properties
- High resistance to ageing

Property	Unit	Data	Audit
Colour		braun	visual
Density at 20°C	kg/m ³	865,0	EN ISO 12185
Viscosity at 40°C	mm ² /s	83,6	DIN 51 562
Viscosity at 100°C	mm ² /s	13,1	DIN 51 562
Viscosity index VI		157	DIN ISO 2909



Property	Unit	Data	Audit
Pourpoint	°C	-39	DIN ISO 3016
Flash point (COC)	°C	228	DIN ISO 2592
TBN	mg KOH/g	12,8	ASTM D2896

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 03. December 2019