



RAVENOL STOU SAE 20W-40



VISCOSITY 20W-40

SPECIFICATIONS API CG-4 | API GL-4

FABRICATION MINERAL

RECOMMENDATIONS FORD M2C-159C | MF M-1143/1144 | MB 227.1 | ZF TE-ML 06B | ZF TE-ML 07B | ALLISON C4 | CATERPILLAR TO-2 | FORD M2C-86A | FORD M2C-134D | JOHN DEERE J 27 | NH 420A | NH 410B

ART.-NR. 1310114

20 L | 1310114-020
20 L | 1310114-B20
1000 L | 1310114-700

RAVENOL STOU SAE 20W-40 is a multi-purpose super tractor oil universal for agricultural machinery, excavators and construction equipment made from specially selected solvent-refined base oils. It is formulated to meet the requirements of all major tractor manufacturers listed below, and can be used in engines, transmissions and hydraulic systems of most tractors in all seasons which require this grade of oil.

Application Notes

RAVENOL STOU SAE 20W-40 has a wide range of applications in engines, transmissions and hydraulic systems of many tractors and is suitable for use as motor oil for both petrol and diesel engines, transmission oil (including wet brakes) and as a hydraulic oil where this specification of product is required.

Characteristics

RAVENOL STOU SAE 20W-40 offers:

- A high dispersion and detergent capability
- Exceptional protection against wear, corrosion and foaming
- High oxidation stability
- Excellent extreme pressure properties
- A high and stable viscosity index

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	883,0	EN ISO 12185
Colour		gelbbraun	visual
Viscosity at 100°C	mm ² /s	13,1	DIN 51 562
Viscosity at 40°C	mm ² /s	111,8	DIN 51 562
Viscosity index VI		112	DIN ISO 2909



Property	Unit	Data	Audit
CCS Viscosity at -15°C	mPa*s	6860	ASTM D5293
Pourpoint	°C	-30	DIN ISO 3016
Flash point (COC)	°C	246	DIN ISO 2592
TBN	mg KOH/g	13,0	ASTM D2896
Sulphated ash	%wt.	1,5	-

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 03. December 2019