



RAVENOL Super HD 50



ART.-NR. 1113305

1 L | 1113305-001
4 L | 1113305-004
5 L | 1113305-005
10 L | 1113305-010
20 L | 1113305-020
20 L | 1113305-B20
60 L | 1113305-060
60 L | 1113305-D60
1000 L | 1113305-700

VISCOSITY 50

SPECIFICATIONS API SF

FABRICATION MINERAL

RECOMMENDATIONS CCMC G2/D1 | MIL-L-46152 B/C | FORD ESE-M2C 153C | FORD SMM-2C 9011A | GM 6085M

RAVENOL Super HD 50 is a mineral mono grade engine oil for passenger car gasoline and diesel engines with and without turbocharging, and is also suitable for commercial vehicle engines and vans under light loads which require this grade of oil.

Designed to minimize friction and wear, the formulation ensures year round high lubricity throughout all operating conditions. Extended oil drain capability where recommended by the vehicle manufacturer.

Application Notes

RAVENOL Super HD 50 is suitable for both gasoline and diesel engines in cars, van and commercial vehicles which require this grade of engine oil.

Characteristics

RAVENOL Super HD 50 offers:

- Good shear stability
- High oxidation stability
- Exceptional viscosity-temperature behavior
- Enhanced levels of detergent and dispersant for cleaner engines
- Very good cold starting properties
- Prevents formation of deposits and black sludge



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	889	EN ISO 12185
Colour		gelbbraun	visual
Viscosity at 100°C	mm ² /s	18,4	DIN 51 562
Viscosity at 40°C	mm ² /s	200,1	DIN 51 562
Viscosity index VI		102	DIN ISO 2909
Pourpoint	°C	-21	DIN ISO 3016
Flash point (COC)	°C	250	DIN ISO 2592
TBN	mg KOH/g	7,4	ASTM D2896

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 03. December 2019