



## RAVENOL Super Truck SAE 10W



ART.-NR. 1123710

20 L | 1123710-020  
20 L | 1123710-B20  
1000 L | 1123710-700

**VISCOSITY** 10W

**SPECIFICATIONS** API CF-4 | ACEA E2 | ACEA B4

**FABRICATION** MINERAL

**RECOMMENDATIONS** MB 228.0 | MAN 270 | MTU TYPE 1 | VOITH DIWA

**RAVENOL Super Truck SAE 10W** is high alloyed HD engine oil with synthetic additives. It is suitable for diesel engines of trucks even with turbo charging. The high additive content guarantees an excellent effect regarding detergent, dispersant and anti corrosion characteristics.

**RAVENOL Super Truck SAE 10W** is a top-quality product with high safety reserves.

## Application Notes

**RAVENOL Super Truck SAE 10W** is mono grade motor oil for use in truck diesel engines with or without turbo charger.

## Characteristics

**RAVENOL Super Truck SAE 10W** offers:

- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety reserves
- Good cold start characteristics
- Best corrosion protection
- Suitable for catalysts
- Reduced emissions

Property	Unit	Data	Audit
Colour		gelbbraun	visual
Density at 20°C	kg/m <sup>3</sup>	864,0	EN ISO 12185
Viscosity at 40°C	mm <sup>2</sup> /s	42,4	DIN 51 562



Property	Unit	Data	Audit
Viscosity at 100°C	mm <sup>2</sup> /s	622	DIN ISO 2909
Pourpoint	°C	-39	DIN ISO 3016
Flash point (COC)	°C	234	DIN ISO 2592

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 03. December 2019