



## RAVENOL Super Truck SAE 20W-20



ART.-NR. 1123715

20 L | 1123715-020  
20 L | 1123715-B20  
1000 L | 1123715-700

**VISCOSITY** 20W-20  
**SPECIFICATIONS** API CF-4 | ACEA E2 | ACEA B4  
**FABRICATION** MINERAL  
**RECOMMENDATIONS** MB 228.0

**RAVENOL Super Truck SAE 20W-20** is high alloyed HD engine oil with synthetic additives. It is suitable for diesel engines of trucks even with turbo charging. The high additive content guarantees an excellent effect regarding detergent, dispersant and anti corrosion characteristics.

**RAVENOL Super Truck SAE 20W-20** is a top-quality product with high safety reserves.

## Application Notes

**RAVENOL Super Truck SAE 20W-20** is multi grade motor oil for use in truck diesel engines with or without turbo charger.

## Characteristics

**RAVENOL Super Truck SAE 20W-20** offers:

- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety reserves
- Good cold start characteristics
- Best corrosion protection
- Suitable for catalysts
- Reduced emissions



Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	870,0	EN ISO 12185
Colour		gelbbraun	visual
Viscosity at 100°C	mm <sup>2</sup> /s	8,7	DIN 51 562
Viscosity at 40°C	mm <sup>2</sup> /s	60,6	DIN 51 562
Viscosity index VI		118	DIN ISO 2909
Pourpoint	°C	-36	DIN ISO 3016
Flash point	°C	240	DIN ISO 2592

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 03. December 2019