



## RAVENOL Super Truck SAE 50



**VISCOSITY** 50  
**SPECIFICATIONS** API CF-4 |API SG |ACEA E2 |ACEA B4  
**FABRICATION** MINERAL

**RAVENOL Super Truck SAE 50** is a modern high alloyed HD engine oil with synthetic additives. It is suitable for diesel engines of trucks even with turbo charging.

**ART.-NR. 1123726**

5 L | 1123726-005  
20 L | 1123726-020  
20 L | 1123726-B20  
208 L | 1123726-208  
208 L | 1123726-D28  
1000 L | 1123726-700

The high additive content guarantees an excellent effect regarding detergent, dispersant and anti corrosion characteristics.

**RAVENOL Super Truck SAE 50** is a top-quality product with high safety reserves.

## Application Notes

**RAVENOL Super Truck SAE 50** is mono grade motor oil for use in truck diesel engines.

Please follow engine manufacturer's recommendations.

## Characteristics

**RAVENOL Super Truck SAE 50** offers:

- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- Good cold start characteristics
- Best corrosion protection
- High safety reserves even with boundary lubrication conditions
- Suitable for catalysts

Property	Unit	Data	Audit
Colour		braun	visual
Density at 20°C	kg/m <sup>3</sup>	887,0	EN ISO 12185



Property	Unit	Data	Audit
Viscosity at 40°C	mm <sup>2</sup> /s	178,3	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	17,3	DIN 51 562
Viscosity index VI		104	DIN ISO 2909
Pourpoint	°C	-18	DIN ISO 3016
Flash point (COC)	°C	258	DIN ISO 2592

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 03. December 2019