



## RAVENOL VSZ Zweitaktoel Vollsynth.



ART.-NR. 1151100

1 L | 1151100-001  
4 L | 1151100-004  
10 L | 1151100-010  
20 L | 1151100-020  
20 L | 1151100-B20  
1000 L | 1151100-700

**SPECIFICATIONS** API TD | ISO-L-EGD

**FABRICATION** FULLY SYNTHETIC

**APPROVALS** JASO FD (049RAV151)

**RECOMMENDATIONS** PIAGGIO SI | 2- STROKE ENGINE AND FOR FAST MOVING HIGH-QUALITY AGGREGATES ( MORE THAN 6000 U/MIN.)

**RAVENOL VSZ Zweitaktoel Vollsynth.** is high quality fully synthetic two-stroke engine oil

**RAVENOL VSZ Zweitaktoel Vollsynth.** with special esters and Polyisobutylene (PIB) and effectively low ash additives for optimum protection against wear and prevent corrosion, deposits and auto-ignitions, even with heavy loads.

## Application Notes

**RAVENOL VSZ Zweitaktoel Vollsynth.** can generally be mixed with regular petrol 1:100.

**RAVENOL VSZ Zweitaktoel Vollsynth.** is best choice for fast moving high-quality aggregates (brush cutters, leaf blowers, etc. with more than 6000 U/min.).

**RAVENOL VSZ Zweitaktoel Vollsynth.** is used for lubrication of air-cooled two-stroke petrol engines with very high speed and heaviest load. Suitable for separate lubrication systems and self-mixing systems.

**RAVENOL VSZ Zweitaktoel Vollsynth.** is also suitable for the lubrication of two stroke scooters with water cooling.

## Characteristics

**RAVENOL VSZ Zweitaktoel Vollsynth.** offers:

- A proper lubrication of all engine parts
- combustion residues and depositsA strong cleaning effect, for clean combustion chambers. Cleans intake and exhaust ports from
- Clean spark plugs provide optimal performance of the engines
- A very high wear and corrosion protection
- Low exhaust emission levels by good combustion
- Very low Pourpoint, also to use at very low temperature



Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	864,0	EN ISO 12185
Colour		braun	visual
Viscosity at 100°C	mm <sup>2</sup> /s	10,8	DIN 51562-1
Viscosity at 40°C	mm <sup>2</sup> /s	70,6	DIN 51562-1
Viscosity index VI		142	DIN ISO 2909
Pourpoint	°C	-48	DIN ISO 3016
Flash point	°C	144	DIN ISO 2592

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 15. September 2020