



RAVENOL WATERCRAFT 4-Takt



SPECIFICATIONS API SG | NMMA FC-W
FABRICATION FULLY SYNTHETIC

RAVENOL WATERCRAFT 4-Takt is a synthetic 4-stroke engine oil based on high quality Polyalphaolefin base oils together with a specialist additive package designed especially for use in marine petrol engines.

RAVENOL WATERCRAFT 4-Takt The formulation ensures optimum oil change intervals, a high corrosion protection and low oil and fuel consumption.

ART.-NR. 1151211

1 L | 1151211-001
4 L | 1151211-004
10 L | 1151211-010
20 L | 1151211-020
20 L | 1151211-B20
1000 L | 1151211-700

Application Notes

RAVENOL WATERCRAFT 4-Takt is suitable for use in water-cooled 4-stroke engines operating in both fresh and sea water environments, and especially where a lubricant is required to meet NMMA FC-W standard.

Follow the manufacturer's recommendations.

Characteristics

RAVENOL Watercraft 4-Takt offers:

- Exceptional corrosion protection in all oil-wetted engine parts
- An adhesive, pressure-and temperature-resistant oil film
- An excellent anti-wear properties
- A strong detergency and clean burning with no deposits
- Low coking
- High wear protection

Property	Unit	Data	Audit
Density at 20°C	kg/m ³	864	EN ISO 12185
Colour		blau	visual



Property	Unit	Data	Audit
Viscosity at 40°C	mm ² /s	98,9	DIN 51 562
Viscosity index VI		148	DIN ISO 2909
Pourpoint	°C	- 30	DIN ISO 3016
TBN	mg KOH/g	8,0	ASTM D2896

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 16. March 2021