



## RAVENOL WATERCRAFT Fullsynth. 2-Takt



ART.-NR. 1151210

1 L | 1151210-001  
4 L | 1151210-004  
10 L | 1151210-010  
20 L | 1151210-020  
20 L | 1151210-B20  
1000 L | 1151210-700

**SPECIFICATIONS** API TD | ISO-L-EGD | JASO FD  
**FABRICATION** FULLY SYNTHETIC  
**APPROVALS** NMMA TC-W3® | RL-29019G

**RAVENOL WATERCRAFT Fullsynth. 2-Takt** is high quality blue coloured fully synthetic two-stroke engine oil. **RAVENOL WATERCRAFT Fullsynth. 2-Takt** is based on polyolester with special esters and Polyisobutylene (PIB) and effectively two stroke additives.

**RAVENOL WATERCRAFT Fullsynth. 2-Takt** is especially developed for two stroke engines in water vehicles.

## Application Notes

**RAVENOL WATERCRAFT Fullsynth. 2-Takt** can generally be mixed with regular petrol 1:100.

**RAVENOL WATERCRAFT Fullsynth. 2-Takt** is used for lubrication of air-cooled two-stroke petrol engines with very high speed and heaviest load.

**RAVENOL WATERCRAFT Fullsynth. 2-Takt -Takt** is also suitable for the lubrication of two stroke scooters with water cooling.

## Characteristics

**RAVENOL WATERCRAFT Fullsynth. 2-Takt** offers:

- A proper lubrication of all engine parts
- A strong cleaning effect, for clean combustion chambers. Cleans intake and exhaust ports from combustion residues and deposits
- Clean spark plugs provide optimal performance of the engines
- A very high wear and corrosion protection
- Low exhaust emission levels by good combustion



Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	864,0	EN ISO 12185
Colour		blau	visual
Viscosity at 100°C	mm <sup>2</sup> /s	10,8	DIN 51 562
Viscosity at 40°C	mm <sup>2</sup> /s	70,7	DIN 51 562
Viscosity index VI		142	DIN ISO 2909
Pourpoint	°C	-48	DIN ISO 3016
Flash point (COC)	°C	143	DIN ISO 2592

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 03. December 2019