



RAVENOL GFE SAE 5W-20



1L | 1111111-001
4L | 1111111-004
10L | 1111111-010
20L | 1111111-020
20L | 1111111-B20
60L | 1111111-060
60L | 1111111-D60
208L | 1111111-208
208L | 1111111-D28
1000L | 1111111-700

Kategorie: Passenger car motor oil

Artikelnummer: 1111111

Viscosity: 5W-20

Specification: API SN Plus, API SP (RC), ILSAC GF-6A

Oil type: Synthetic

Approvals: API SN Plus, API SP Resource Conserving, GM dexos1™ Gen 2 (Lizenz-Nr. D10887IG081), ILSAC GF-6A

Recommendation: Chrysler MS-13340, Chrysler MS-6395, Ford WSS-M2C945-B1, Ford WSS-M2C960-A1

Application: Passenger car

Technology: Clean Synto®

RAVENOL GFE SAE 5W-20 is a synthetic, low-friction engine oil with CleanSynto® technology for passenger car gasoline and diesel engines, with and without turbocharging and direct injection.

RAVENOL GFE SAE 5W-20 achieves a high viscosity index through its formulation with special base oils. The excellent cold start behaviour provides an optimum lubricating safety during the cold run phase.

Because of a considerable fuel saving **RAVENOL GFE SAE 5W-20** contributes to protect the environment by reducing the emissions.

RAVENOL GFE SAE 5W-20 minimizes friction, wear and fuel consumption with excellent cold start characteristics.

RAVENOL GFE SAE 5W-20 also meets the specification WSS-M2C945-B1 and API SN PLUS, therefore it can reduce the problem of oil derived low speed pre-ignition.

Suitable for extended oil change intervals where recommended by manufacturer.

Application Note

RAVENOL GFE SAE 5W-20 is an universal fuel-efficient engine oil, a top-quality product for modern passenger cars with gasoline and diesel engines.

Characteristics

- Guaranteed fastest possible lubrication of the engine.
- High fuel economy (FE) effect due to the base oils and additives used. Low volatilization tendency,
- thereby lower oil consumption.
- Can reduce oil derived low speed pre-ignition.
- Provides protection against sludging, coking, varnish and corrosion even under unfavorable operating conditions.

- No oil-related deposits in combustion chambers in the piston ring zone and on valves.
- Ensures the function of the hydraulic tappets at all temperatures.
- Stable engine oil, no NOx oxidation.
- Good soot absorption and dispersion.
- Neutral towards sealing materials.

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	846,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	8,6	DIN 51562-1
Viscosity at 40 °C	mm ² /s	47,1	DIN 51562-1
Viscosity Index VI		163	DIN ISO 2909
HTHS Viscosity at 150 °C	mPa*s	2,94	ASTM D5481
CCS Viscosity at -30 °C	mPa*s	3650	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -35 °C	mPa*s	9.630	ASTM D4684
Pourpoint	°C	-42	DIN ISO 3016
Noack Volatility	% M/M	8,4	ASTM D5800
Flashpoint	°C	232	DIN EN ISO 2592
tbn	mg KOH/g	8,8	ASTM D2896
Sulphated Ash	%wt.	0,86	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.

05.10.2022