



RAVENOL 4-Takt Gardenoil

Kategorie: Other engine oil

Artikelnummer: 1113301

Viscosity: 30

Specification: API CD, API SF

Oil type: Mineral

Recommendation: CCMC G4, Honda, Husqvarna, MB 227.0, MIL-L-2104 D, MIL-L-46152 B, Oleo-Mac, Stihl

Application: Hobby and garden



RAVENOL 4-Takt Gardenoil HD 30 is a mineral mono grade engine oil formulated for use in 4-stroke lawn mowers. Special additives ensure an excellent protection against wear and corrosion. Usable at normal operating temperatures. Constant viscosity, no shearing losses.

RAVENOL 4-Takt Gardenoil HD 30 usable especially where the normal operating temperatures will be expected. The oil viscosity remains constantly at the operation temperature over the whole service interval.

1L | 1113301-001

4L | 1113301-004

5L | 1113301-005

10L | 1113301-010

20L | 1113301-020

20L | 1113301-B20

60L | 1113301-060

208L | 1113301-208

1000L | 1113301-700

Application Note

RAVENOL 4-Takt Gardenoil HD 30 is suitable for use in 4-stroke lawn mowers under normal operating temperatures.

Characteristics

- Protection against corrosion
- Good shear stability
- High oxidation stability
- Excellent viscosity-temperature behavior
- Enhanced levels of detergent and dispersant for cleaner engines
- Very good cold starting properties
- Prevents formation of deposits and black sludge

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	876,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	11,6	DIN 51562-1
Viscosity at 40 °C	mm ² /s	94,4	DIN 51562-1
Viscosity Index VI		111	DIN ISO 2909
Pourpoint	°C	-24	DIN ISO 3016
Flashpoint	°C	248	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.

27.01.2023