



RAVENOL Spezial Diesel SAE 10W-30



Kategorie: Truck engine oil

Artikelnummer: 1113310

Viscosity: 10W-30

Specification: ACEA B2, API CD

Oil type: Mineral

Recommendation: CCMC G4, MB 227.1, MIL-L-2104 D, MIL-L-46152 B

Application: Passenger car, Truck, Agricultural machinery, Hobby and garden

RAVENOL Spezial Diesel SAE 10W-30 is an excellent multi-grade engine oil for use in passenger vehicle and truck engines. It meets the requirements of modern diesel engines with and without induction. The favourable viscosity range ensures high lubricity year-round under different operating conditions.

Application Note

Use **RAVENOL Spezial Diesel SAE 10W-30** according to the specifications of the diesel engine manufacturer.

Characteristics

- Corrosion protection
- Excellent shearing stability
- High oxidation stability
- Excellent viscosity-temperature attribute•Compelling detergent- and dispersant properties
- Compelling detergent- and dispersant properties
- High safety reserves even in boundary lubrication
- Neutral to sealants
- Excellent cold starting properties
- Prevents adhesion, lacquering, carbonisation and sludge (black sludge) from forming on cylinders,pistons, valves, spark plugs and turbochargers
- Suitable for use in vehicles with catalytic converters

1L | 1113310-001

4L | 1113310-004

5L | 1113310-005

10L | 1113310-010

20L | 1113310-020

20L | 1113310-B20

60L | 1113310-060

208L | 1113310-208

1000L | 1113310-700

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	859,0	EN ISO 12185
Colour		braun	VISUELL
Viscosity at 100 °C	mm ² /s	11,5	DIN 51562-1
Viscosity at 40 °C	mm ² /s	78,2	DIN 51562-1
Viscosity Index VI		142	DIN ISO 2909
Pourpoint	°C	-33	DIN ISO 3016
Flashpoint	°C	244	DIN EN ISO 2592
tbn	mg KOH/g	7,1	ASTM D2896
Sulphated Ash	%wt.	0,8	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.

07.02.2023