



# RAVENOL SVT Stand. Viscosity Turbo Oil SAE 10W-40



1L | 1116103-001  
5L | 1116103-005  
10L | 1116103-010  
20L | 1116103-020  
20L | 1116103-B20  
60L | 1116103-060  
60L | 1116103-D60  
208L | 1116103-208

**Kategorie:** Passenger car motor oil

**Artikelnummer:** 1116103

**Viscosity:** 10W-40

**Specification:** ACEA A3/B4, API CF, API SM

**Oil type:** Semi-synthetic

**Recommendation:** BMW Special Oil, MB 229.1, VW 500 00, VW 501 00, VW 502 00, VW 505 00

**Application:** Passenger car

**RAVENOL SVT Standard Viscosity Turbo Oil SAE 10W-40** features outstanding lubrication and excellent shear stability, and the added conditioners simultaneously reduce oil consumption and protect from sludge and wear.

The semi synthetic motor oil **RAVENOL SVT Standard Viscosity Turbo Oil SAE 10W-40** is a new development with a unique formula specifically for high mileage vehicles of approx. 100,000 km and more.

**RAVENOL SVT Standard Viscosity Turbo Oil SAE 10W-40** is particularly recommended for vehicles with high mileage, petrol and diesel engines, with and without turbocharge and direct injection.

The extremely conditioning and cleaning additives in **RAVENOL SVT Standard Viscosity Turbo Oil SAE 10W-40** revitalise critical engine parts and particularly protect gaskets. This can extend the life, particularly in older vehicles with high mileage.

## Application Note

**RAVENOL SVT Standard Viscosity Turbo Oil SAE 10W-40** is perfectly suited for year-round use in high mileage petrol and diesel engines with 100,000 km and more, and promotes low oil consumption. A very clean engine is guaranteed.

**RAVENOL SVT Standard Viscosity Turbo Oil SAE 10W-40** extends the life of the engine in older vehicles by reducing oil consumption and protecting from sludge and wear. A very clean engine is guaranteed.

## Characteristics

- High wear protection, important for high mileage and inadequate oil changes
- Fuel saving because of easy running characteristics
- Outstanding detergent and dispersant properties prevent sludge
- High oxidation stability for a long life
- Brilliant cold cranking behaviour through special additives
- Excellent viscosity-temperature behaviour
- Low vaporisation characteristics, therefore reduced oil consumption
- Suitable for catalytic converters

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m <sup>3</sup>	862,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	13,9	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	93,2	DIN 51562-1
Viscosity Index VI		151	DIN ISO 2909
HTHS Viscosity at 150 °C	mPa*s	4,03	ASTM D5481
CCS Viscosity at -25 °C	mPa*s	4900	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -30 °C	mPa*s	18.000	ASTM D4684
Pourpoint	°C	-36	DIN ISO 3016
Noack Volatility	% wt.	9,5	ASTM D5800
Flashpoint	°C	238	DIN EN ISO 2592
tbn	mg KOH/g	10,1	ASTM D2896
Sulphated Ash	%wt.	1,3	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.