



RAVENOL SVT Stand. Viscosity Turbo Oil SAE 10W-40



1L | 1116103-001
5L | 1116103-005
20L | 1116103-020
20L | 1116103-B20
60L | 1116103-060
60L | 1116103-D60
208L | 1116103-208

Kategorie: Passenger car motor oil

Artikelnummer: 1116103

Viscosity: 10W-40

Specification: ACEA A3/B4, API CF, API SM

Oil type: Semi-synthetic

Recommendation: BMW Special Oil, MB 229.1, VW 500 00, VW 501 00, VW 502 00, VW 505 00

Application: Passenger car

RAVENOL SVT Standard Viscosity Turbo Oil SAE 10W-40 features outstanding lubrication and excellent shear stability, and the added conditioners simultaneously reduce oil consumption and protect from sludge and wear.

The semi synthetic motor oil **RAVENOL SVT Standard Viscosity Turbo Oil SAE 10W-40** is a new development with a unique formula specifically for high mileage vehicles of approx. 100,000 km and more.

RAVENOL SVT Standard Viscosity Turbo Oil SAE 10W-40 is particularly recommended for vehicles with high mileage, petrol and diesel engines, with and without turbocharge and direct injection.

The extremely conditioning and cleaning additives in **RAVENOL SVT Standard Viscosity Turbo Oil SAE 10W-40** revitalise critical engine parts and particularly protect gaskets. This can extend the life, particularly in older vehicles with high mileage.

Application Note

RAVENOL SVT Standard Viscosity Turbo Oil SAE 10W-40 is perfectly suited for year-round use in high mileage petrol and diesel engines with 100,000 km and more, and promotes low oil consumption. A very clean engine is guaranteed.

RAVENOL SVT Standard Viscosity Turbo Oil SAE 10W-40 extends the life of the engine in older vehicles by reducing oil consumption and protecting from sludge and wear. A very clean engine is guaranteed.

Characteristics

- High wear protection, important for high mileage and inadequate oil changes
- Fuel saving because of easy running characteristics
- Outstanding detergent and dispersant properties prevent sludge? High
- High oxidation stability for a long life
- Brilliant cold cranking behaviour through special additives
- Excellent viscosity-temperature behaviour
- Low vaporisation characteristics, therefore reduced oil consumption

- Suitable for catalytic converters

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	862,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	13,9	DIN 51562-1
Viscosity at 40 °C	mm ² /s	93,2	DIN 51562-1
Viscosity Index VI		151	DIN ISO 2909
Pourpoint	°C	-36	DIN ISO 3016
Flashpoint	°C	238	DIN EN ISO 2592
tbn	mg KOH/g	10,1	ASTM D2896
Sulphated Ash	%wt.	1,3	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.

02.12.2022