



RAVENOL Super Performance Truck SAE 5W-30



1L | 1122102-001
5L | 1122102-005
10L | 1122102-010
20L | 1122102-020
20L | 1122102-B20
60L | 1122102-060
60L | 1122102-D60
208L | 1122102-208
208L | 1122102-D28
1000L | 1122102-700

Kategorie: Truck engine oil

Artikelnummer: 1122102

Viscosity: 5W-30

Specification: ACEA E4, ACEA E7, API CF

Oil type: Synthetic

Approvals: API CI-4, Renault RXD

Recommendation: Cummins CES 20076, Cummins CES 20077, Cummins CES 20078, Global DHD-1, IVECO, JASO DH-1, Mack EO-M Plus, MAN M 3277, MB 228.5, MB 235.28, MTU Typ 3, Scania LDF-3, Voith Retarder B, VOLVO VDS-3

Application: Truck

RAVENOL Super Performance Truck SAE 5W-30 is a high alloyed USHPD low friction engine oil for commercial vehicles. Because of the use of synthetic basic oils the viscosity area 5W-30 could be realised. Because of the cold viscosity SAE 5W a definite cold start (low cold start corrosion) and a supply of all lubrication areas is guaranteed as quickly as possible at very low outside temperatures. Extreme stress applications are controlled by the high temperature viscosity SAE 30. Minimized friction loss and wear.

Application Note

RAVENOL Super Performance Truck SAE 5W-30 is a high-performance engine oil for commercial vehicles which can be used the whole year and which is adapted to the new exhaust gas emission rules (also for EURO I, II, III, IV and EURO V engines).

RAVENOL Super Performance Truck SAE 5W-30 is suitable for oil change intervals up to more than 100.000 km according to the manufacturer's specifications.

Characteristics

- Protection against corrosion
- An excellent oxidation stability
- An excellent high temperature stability
- Excellent detergent and dispersant attributes
- Profitability because of a low fuel consumption
- Long endurance because of a high oxidation stability
- Excellent cold start attributes
- A very good viscosity temperature behaviour
- Low evaporation

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	854,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	11,5	DIN 51562-1
Viscosity at 40 °C	mm ² /s	69,3	DIN 51562-1
Viscosity Index VI		161	DIN ISO 2909
CCS Viscosity at -30 °C	mPa*s	6000	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -35 °C	mPa*s	16.200	ASTM D4684
Pourpoint	°C	-36	DIN ISO 3016
Noack Volatility	% M/M	10,1	ASTM D5800
Flashpoint	°C	242	DIN EN ISO 2592
tbn	mg KOH/g	13,0	ASTM D2896
Sulphated Ash	%wt.	1,0	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.

02.10.2022