



RAVENOL Standard Truck SAE 10W



20L | 1123610-020
 20L | 1123610-B20
 60L | 1123610-060
 208L | 1123610-208

Kategorie: Truck engine oil

Artikelnummer: 1123610

Viscosity: 10W

Specification: API CF, API SF

Oil type: Mineral

Recommendation: Allison C4, Caterpillar TO-2, MAN 270, MB 227.0, MIL-L-2104 E, MTU Typ 1, Voith DIWA, Voith Retarder A, ZF TE-ML 02C, ZF TE-ML 03B, ZF TE-ML 04B, ZF TE-ML 06A, ZF TE-ML 07D

Application: Truck

RAVENOL Standard Truck SAE 10W is mineral mono grade motor oil for trucks. All-season oil for all truck diesel engine types. High protection against friction and abrasion, excellent cold start characteristics. Extended oil change intervals according to manufacturer's recommendations.

Application Note

RAVENOL Standard Truck SAE 10 is mono grade motor oil for use in truck diesel engines. Also suitable for stationary plants.

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	862,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	6,4	DIN 51562-1
Viscosity at 40 °C	mm ² /s	36,9	DIN 51562-1
Viscosity Index VI		123	DIN ISO 2909
Pourpoint	°C	-36	DIN ISO 3016
Flashpoint	°C	232	DIN EN ISO 2592
tbn	mg KOH/g	21,0	ASTM D2896

All indicated data are approximate values and are subject to the commercial fluctuations.